

DEVOTE 0



SPECIFICATIES

FRAME	
MATEN	XS, S, M, L
KLEUREN	Sandshell
FRAME	ALUXX-grade aluminum, 12x142mm thru-axle, flat mount disc, flip chip – dropout
VOORVORK	Advanced-grade composite, full-composite OverDrive steerer, 12mm thru-axle, flat mount disc
DEMPER	N/A
ONDERDELEN	
STUUR	Giant Contact XR D-Fuse, 31.8mm, 5-degree back sweep, flare drop, alloy XS: 400mm, S: 400mm, M: 420mm, L: 420mm
HANDVATTEN	cork tape with gel
STUURPEN	Giant Contact, +/- 8 degree, alloy XS: 50mm, S: 60mm, M: 70mm, L: 80mm
ZADELLEN	Giant Contact D-Fuse, alloy, 14mm offset
ZADEL	Liv Approach
PEDALEN	N/A
AFMONTAGE	
SHIFTERS	Shimano GRX RX-610, 2x12
VOORDERAILLEUR	Shimano GRX RX-820
ACHTERDERAILLEUR	Shimano GRX RX-820
REMMEN	Shimano GRX BR-RX410 hydraulic, Giant MPH rotors [F]160mm, [R]160mm
REMHENDELS	Shimano GRX RX-610 hydraulic
CASSETTE	Shimano 105, 12-speed, 11x34
AANDRIJVING	KMC X12L-1
CRANKSET	FSA Omega Modular AGX+, 32/48 XS: 165mm, S: 170mm, M: 172.5mm, L: 172.5mm
BOTTOM BRACKET	FSA Mega EXA

WIELSET	
VELGEN	Giant S-X2 Disc wheelset, alloy
NAVEN	Giant alloy, 12mm thru-axle
SPAKEN	stainless
BANDEN	Maxxis Rambler 700x40c, tubeless
EXTRA'S	53mm max tire size in long flip chip position, 45mm max tire size in short flip chip position, tubeless prepared, ISC clamp

Adviesprijs: € 1.949,00

GEOMETRIE

FRAME	XS	S	M	L
	SHORT LONG	SHORT LONG	SHORT LONG	SHORT LONG
Zitbuis lengte (mm)	390	420	465	500
Zitbuis hoek	74,5° 74,4°	74,5° 74,4°	74,5° 74,4°	74,5° 74,4°
Frame Lengte (horizontaal) (mm)	525 525	535 535	545 545	555 555
Balhoofdbuis Lengte (mm)	90	110	140	160
Balhoofdbuis Hoek	70,0° 69,9°	70,5° 70,4°	71,0° 70,9°	71,0° 70,9°
Vork Sprong (mm)	50	50	50	50
Naloop (mm)	78,4 82	75 78,5	71,6 75,1	71,6 75
Wielbasis (mm)	1017 1027	1024 1034	1031 1041	1043 1052
Liggende achtersvork lengte (mm)	430 440	430 440	430 440	430 440
Bottom Bracket Drop (mm)	80 81	80 81	80 81	80 81
Stack (mm)	523 524	544 545	574 575	593 594
Reach (mm)	380 379	384 383	386 385	391 389
Stand Over Height (mm)	681 688	708 715	748 755	779 786
Stuur breedte (mm)	400	400	420	420
Stuurpen Lengte (mm)	50	60	70	80
Cranklengte (mm)	165	170	172,5	172,5
Wielmaat	700	700	700	700

Deze specificaties zijn met de grootste zorgvuldigheid samengesteld. Specificaties, beschikbaarheid, prijzen en kleuren kunnen echter zonder voor aankondiging wijzigen.