

# DEVOTE 0



## SPECIFICATIES

FRAME	
MATEN	XS, S, M, L
KLEUREN	Clear Sky
FRAME	ALUXX-grade aluminum, 12x142mm thru-axle, flat mount disc, flip chip – dropout
VOORVORK	Advanced-grade composite, full-composite OverDrive steerer, 12mm thru-axle, flat mount disc
DEMPER	N/A
ONDERDELEN	
STUUR	Giant Contact XR D-Fuse, 31.8mm, 5-degree back sweep, flare drop, XS: 400mm, S: 400mm, M: 420mm, L: 420mm
HANDVATTEN	Cork Tape w/ Gel VLT004-02
STUURPEN	Giant Contact, 8-degree, XS: 50mm, S: 60mm, M: 70mm, L: 80mm
ZADELPEEN	Giant D-Fuse, alloy
ZADEL	Liv Grit
AFMONTAGE	
SHIFTERS	Shimano GRX RX-610, 2x12
VOORDERAILLEUR	Shimano GRX RX-820
ACHTERDERAILLEUR	Shimano GRX RX-820
REMMEN	Shimano GRX BR-RX410 hydraulic, Giant MPH rotors, [F]160mm, [R]160mm
REMHENDELS	Shimano GRX RX-610 hydraulic
CASSETTE	Shimano 105, 12-speed, 11x34
AANDRIJVING	KMC X12L-1
CRANKSET	Shimano FC-RX610, 30/46, XS: 165mm, S: 170mm, M: 172.5mm, L: 172.5mm
BOTTOM BRACKET	Shimano, press fit

WIELSET	
VELGEN	Giant S-X2 Disc, alloy
NAVEN	Giant alloy, 12mm thru-axle
SPAKEN	stainless steel
BANDEN	CrossCut GRIP 1; 700x45c
EXTRA'S	53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position, tubeless prepared, ISC clamp
LIMITS	
MAX TIRE CLEARANCE	53mm

Adviesprijs: € 1.999,00

## GEOMETRIE

FRAME	XS	S	M	L
	SHORT   LONG	SHORT   LONG	SHORT   LONG	SHORT   LONG
Zitbuis lengte (mm)	390	420	465	500
Zitbuis hoek	74,5°   74,4°	74,5°   74,4°	74,5°   74,4°	74,5°   74,4°
Frame Lengte (horizontaal) (mm)	525   525	535   535	545   545	555   555
Balhoofdbuis Lengte (mm)	90	110	140	160
Balhoofdbuis Hoek	70,0°   69,9°	70,5°   70,4°	71,0°   70,9°	71,0°   70,9°
Vork Sprong (mm)	50	50	50	50
Naloop (mm)	78,4   82	75   78,5	71,6   75,1	71,6   75
Wielbasis (mm)	1017   1027	1024   1034	1031   1041	1043   1052
Liggende achtervork lengte (mm)	430   440	430   440	430   440	430   440
Bottom Bracket Drop (mm)	80   81	80   81	80   81	80   81
Stack (mm)	523   524	544   545	574   575	593   594
Reach (mm)	380   379	384   383	386   385	391   389
Stand Over Height (mm)	681   688	708   715	748   755	779   786
Stuur breedte (mm)	400	400	420	420
Stuurpen Lengte (mm)	50	60	70	80
Cranklengte (mm)	165	170	172,5	172,5

Deze specificaties zijn met de grootste zorgvuldigheid samengesteld. Specificaties, beschikbaarheid, prijzen en kleuren kunnen echter zonder voorafkondiging wijzigen.