

DEVOTE 0



SPECS

RAM	
STORLEKAR	XS, S, M, L
FÄRGER	Clear Sky
RAM	ALUXX-grade aluminum, 12x142mm thru-axle, flat mount disc, flip chip – dropout
GAFFEL	Advanced-grade composite, full-composite OverDrive steerer, 12mm thru-axle, flat mount disc
BAKDÄMPARE	N/A
KOMPONENTER	
STYRE	Giant Contact XR D-Fuse, 31.8mm, 5-degree back sweep, flare drop, XS: 400mm, S: 400mm, M: 420mm, L: 420mm
GREPPAR	Cork Tape w/ Gel VLT004-02
STAM	Giant Contact, 8-degree, XS: 50mm, S: 60mm, M: 70mm, L: 80mm
SADELSTOLPE	Giant D-Fuse, alloy
SADEL	Liv Grit
DRIVLINA	
VÄXLAR	Shimano GRX RX-610, 2x12
FRAMVÄXEL	Shimano GRX RX-820
BAKVÄXEL	Shimano GRX RX-820
BROMSAR	Shimano GRX BR-RX410 hydraulic, Giant MPH rotors, [F]160mm, [R]160mm
BROMSSPAKAR	Shimano GRX RX-610 hydraulic
KASSETT	Shimano 105, 12-speed, 11x34
KEDJA	KMC X12L-1
VEVPARTI	Shimano FC-RX610, 30/46, XS: 165mm, S: 170mm, M: 172.5mm, L: 172.5mm
BROMSREGLAGE	Shimano, press fit

HJUL	
FÄLGAR	Giant S-X2 Disc, alloy
NAV	Giant alloy, 12mm thru-axle
EKRAR	stainless steel
DÄCK	CrossCut GRIP 1; 700x45c
EXTRAFUNKTIONER	53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position, tubeless prepared, ISC clamp
GRÄNSER	
MAX DÄCKAVSTÅND	53mm

Price: 23 990,00 kr

GEOMETRY

RAM	XS		S		M		L	
	SHORT	LONG	SHORT	LONG	SHORT	LONG	SHORT	LONG
Längd sadelrör (mm)	390	420	465	500				
Vinkel sadelrör	74,5° 74,4°	74,5° 74,4°	74,5° 74,4°	74,5° 74,4°				
Topprörets längd (mm)	525 525	535 535	545 545	555 555				
Styrhuvud Längd (mm)	90	110	140	160				
Vinkel styrhuvud	70,0° 69,9°	70,5° 70,4°	71,0° 70,9°	71,0° 70,9°				
Gaffelvinkel (mm)	50	50	50	50				
Spår (mm)	78,4 82	75 78,5	71,6 75,1	71,6 75				
Hjulbas (mm)	1017 1027	1024 1034	1031 1041	1043 1052				
Kedjestagslängd (mm)	430 440	430 440	430 440	430 440				
Nedre fäste Drop (mm)	80 81	80 81	80 81	80 81				
Stack (mm)	523 524	544 545	574 575	593 594				
Reach (mm)	380 379	384 383	386 385	391 389				
Stå över höjden (mm)	681 688	708 715	748 755	779 786				
Styrets bredd (mm)	400	400	420	420				
Stamlängd (mm)	50	60	70	80				
Vevlängd (mm)	165	170	172,5	172,5				

All specifications listed are subject to change without notice.