

DEVOTE 1



СПЕЦИФИКАЦИИ

РАМКА	
РАЗМЕР	XS, S, M, L
ЦВЯТ	Dune Beige
РАМКА	ALUXX-grade aluminum, 12x142mm thru-axle, flat mount disc, flip chip – dropout
ВИЛКА	Advanced-grade composite, full-composite OverDrive steerer, 12mm thru-axle, flat mount disc
ЗАДЕН АМОРТИСЬОР	N/A
КОМПОНЕНТИ	
КОРМИЛО	Giant Contact XR D-Fuse, 31.8mm, 5-degree back sweep, flare drop, XS: 400mm, S: 400mm, M: 420mm, L: 420mm
ГРИПОВЕ	Cork Tape w/ Gel VLT004-02
ЛАПА	Giant Contact, 8-degree, XS: 50mm, S: 60mm, M: 70mm, L: 80mm
КОЛЧЕ ЗА СЕДАЛКА	Giant D-Fuse, alloy
СЕДАЛКА	Liv Grit
DRIVETRAIN	
КОМАНДИ	Shimano CUES U6030, 2x10
ПРЕДЕН ДЕРАЙЛЪОР	Shimano CUES U6030
ЗАДЕН ДЕРАЙЛЪОР	Shimano CUES U6020
СПИРАЧКИ	Shimano CUES BR-U6030 hydraulic, Giant MPH rotors, [F]160mm, [R]160mm
РЪКОХВАТКИ ЗА СПИРАЧКИ	Shimano CUES BR-U6030 hydraulic
КАСЕТА	Shimano CS-LG300, 11x39
ВЕРИГА	KMC X11 with Missing Link
КУРБЕЛ	Shimano FC-U6030, 32/46, XS: 165mm, S: 170mm, M: 172.5mm, L: 172.5mm
СРЕДНА КАСЕТА	Shimano, press fit

КАПЛИ	
ШИНИ	Giant S-X2 Disc, alloy
ГЛАВИНИ	Giant alloy, 12mm thru-axle
СПИЦИ	stainless steel
ГУМИ	CrossCut GRIP 1; 700x45c
ЕКСТРИ	53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position, tubeless prepared, ISC clamp
ЛИМИТИ	
MAX TIRE CLEARANCE	53mm

ГЕОМЕТРИЯ

РАМКА	XS	S	M	L
	SHORT LONG	SHORT LONG	SHORT LONG	SHORT LONG
Seat Tube Length (mm)	390	420	465	500
Seat Tube Angle	74,5° 74,4°	74,5° 74,4°	74,5° 74,4°	74,5° 74,4°
Top Tube Length (mm)	525 525	535 535	545 545	555 555
Head Tube Length (mm)	90	110	140	160
Head Tube Angle	70,0° 69,9°	70,5° 70,4°	71,0° 70,9°	71,0° 70,9°
Fork Rake (mm)	50	50	50	50
Trail (mm)	78,4 82	75 78,5	71,6 75,1	71,6 75
Wheelbase (mm)	1017 1027	1024 1034	1031 1041	1043 1052
Chain Stay Length (mm)	430 440	430 440	430 440	430 440
Bottom Bracket Drop (mm)	80 81	80 81	80 81	80 81
Stack (mm)	523 524	544 545	574 575	593 594
Обсер (mm)	380 379	384 383	386 385	391 389
Stand Over Height (mm)	681 688	708 715	748 755	779 786
Ширина на Кормило (mm)	400	400	420	420
Дължина на Лапа (mm)	50	60	70	80
Дължина на Курбел (mm)	165	170	172,5	172,5

All specifications listed are subject to change without notice.