



SPECIFIKATIONER

RAMME	
STØRRELSER	XS, S, M, L
FARVER	Dune Beige
RAMME	ALUXX-grade aluminum, 12x142mm thru-axle, flat mount disc, flip chip – dropout
FORGAFFEL	Advanced-grade composite, full-composite OverDrive steerer, 12mm thru-axle, flat mount disc
BAGDÆMPER	N/A
KOMPONENTER	
STYR	Giant Contact XR D-Fuse, 31.8mm, 5-degree back sweep, flare drop, XS: 400mm, S: 400mm, M: 420mm, L: 420mm
GREB / STYRBÅND	Cork Tape w/ Gel VLT004-02
FREMPIND	Giant Contact, 8-degree, XS: 50mm, S: 60mm, M: 70mm, L: 80mm
SADELPIND	Giant D-Fuse, alloy
SADEL	Liv Grit
GEARGRUPPE	
SKIFTEGREB	Shimano CUES U6030, 2x10
FORSKIFTER	Shimano CUES U6030
BAGSKIFTER	Shimano CUES U6020
BREMSER	Shimano CUES BR-U6030 hydraulic, Giant MPH rotors, [F]160mm, [R]160mm
BREMSEGREB	Shimano CUES BR-U6030 hydraulic
KASSETTE	Shimano CS-LG300, 11x39
KÆDE	KMC X11 with Missing Link
KRANKSÆT	Shimano FC-U6030, 32/46, XS: 165mm, S: 170mm, M: 172.5mm, L: 172.5mm
KRANKBOKS	Shimano, press fit

HJUL	
FÆLGE	Giant S-X2 Disc, alloy
NAV	Giant alloy, 12mm thru-axle
EGER	stainless steel
DÆK	CrossCut GRIP 1; 700x45c
EKSTRA	53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position, tubeless prepared, ISC clamp
GRÆNSER	
MAX DÆKSTØRRELSE	53mm

Pris: 13.899,00 kr.

GEOMETRI

RAMME	XS		S		M		L	
	SHORT	LONG	SHORT	LONG	SHORT	LONG	SHORT	LONG
Sadelrørslængde (mm)	390	420	465	500				
Sadelrørsvinkel	74,5° 74,4°	74,5° 74,4°	74,5° 74,4°	74,5° 74,4°				
Overrørslængde (mm)	525 525	535 535	545 545	555 555				
Kronrørslængde (mm)	90	110	140	160				
Kronrørsvinkel	70,0° 69,9°	70,5° 70,4°	71,0° 70,9°	71,0° 70,9°				
Forgaffel fremspring (rake) (mm)	50	50	50	50				
Sti (mm)	78,4 82	75 78,5	71,6 75,1	71,6 75				
Akselafstand (mm)	1017 1027	1024 1034	1031 1041	1043 1052				
Kædestagslængde (mm)	430 440	430 440	430 440	430 440				
Krankboks drop (mm)	80 81	80 81	80 81	80 81				
Stack (mm)	523 524	544 545	574 575	593 594				
Reach (mm)	380 379	384 383	386 385	391 389				
Skridthøjde (mm)	681 688	708 715	748 755	779 786				
Styrbredde (mm)	400	400	420	420				
Frempindslængde (mm)	50	60	70	80				
Pedalarmslængde (mm)	165	170	172,5	172,5				

Alle de anførte specifikationer kan ændres uden varsel.