

DEVOTE 1



SPECS

ΣΚΕΛΕΤΟΣ	
ΜΕΓΕΘΗ	XS, S, M, L
ΧΡΩΜΑΤΑ	Dune Beige
ΣΚΕΛΕΤΟΣ	ALUXX-grade aluminum, 12x142mm thru-axle, flat mount disc, flip chip – dropout
ΠΙΡΟΥΝΙ	Advanced-grade composite, full-composite OverDrive steerer, 12mm thru-axle, flat mount disc
ΑΝΑΡΤΗΣΗ	N/A
ΕΞΑΡΤΗΜΑΤΑ	
ΤΙΜΟΝΙ	Giant Contact XR D-Fuse, 31.8mm, 5-degree back sweep, flare drop, XS: 400mm, S: 400mm, M: 420mm, L: 420mm
GRIPS	Cork Tape w/ Gel VLT004-02
ΛΑΙΜΟΣ ΤΙΜΟΝΙΟΥ	Giant Contact, 8-degree, XS: 50mm, S: 60mm, M: 70mm, L: 80mm
ΛΑΙΜΟΣ ΣΕΛΛΑΣ	Giant D-Fuse, alloy
ΣΕΛΛΑ	Liv Grit
ΜΕΤΑΔΟΣΗ	
ΛΕΒΙΕ ΤΑΧΥΤΗΤΩΝ	Shimano CUES U6030, 2x10
ΝΤΕΡΑΓΙΕΣ ΕΜΠΡΟΣΘΙΟ	Shimano CUES U6030
ΝΤΕΡΑΓΙΕΣ ΟΠΙΣΘΙΟ.	Shimano CUES U6020
ΦΡΕΝΑ	Shimano CUES BR-U6030 hydraulic, Giant MPH rotors, [F]160mm, [R]160mm
ΜΑΝ'ΕΤΤΕΣ ΦΡΕΝΩΝ	Shimano CUES BR-U6030 hydraulic
CASETTE Ή ΕΛΕΥΘΕΡΟ	Shimano CS-LG300, 11x39
ΑΛΥΣΙΔΑ	KMC X11 with Missing Link
ΔΙΣΚΟΒΡΑΧΙΩΝΑΣ	Shimano FC-U6030, 32/46, XS: 165mm, S: 170mm, M: 172.5mm, L: 172.5mm
BOTTOM BRACKET	Shimano, press fit

WHEELS	
ΣΤΕΦΑΝΙΑ	Giant S-X2 Disc, alloy
ΚΕΝΤΡΑ	Giant alloy, 12mm thru-axle
ΑΚΤΙΝΕΣ	stainless steel
ΕΛΑΣΤΙΚΑ	CrossCut GRIP 1; 700x45c
EXTRAS	53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position, tubeless prepared, ISC clamp
LIMITS	
MAX TIRE CLEARANCE	53mm

ΓΕΩΜΕΤΡΙΑ

ΣΚΕΛΕΤΟΣ	XS		S		M		L	
	SHORT	LONG	SHORT	LONG	SHORT	LONG	SHORT	LONG
Seat Tube Length (mm)	390		420		465		500	
Seat Tube Angle	74,5°	74,4°	74,5°	74,4°	74,5°	74,4°	74,5°	74,4°
Top Tube Length (mm)	525	525	535	535	545	545	555	555
Head Tube Length (mm)	90		110		140		160	
Head Tube Angle	70,0°	69,9°	70,5°	70,4°	71,0°	70,9°	71,0°	70,9°
Fork Rake (mm)	50		50		50		50	
Trail (mm)	78,4	82	75	78,5	71,6	75,1	71,6	75
Wheelbase (mm)	1017	1027	1024	1034	1031	1041	1043	1052
Chain Stay Length (mm)	430	440	430	440	430	440	430	440
Bottom Bracket Drop (mm)	80	81	80	81	80	81	80	81
Stack (mm)	523	524	544	545	574	575	593	594
Reach (mm)	380	379	384	383	386	385	391	389
Stand Over Height (mm)	681	688	708	715	748	755	779	786
Handlebar Width (mm)	400		400		420		420	
Stem Length (mm)	50		60		70		80	
Crank Length (mm)	165		170		172,5		172,5	

Όλες οι προδιαγραφές είναι δυνατό να αλλάξουν χωρίς πρότερη ειδοποίηση