



## SPECS

FRAME	
<b>SIZES</b>	XS, S, M, L
<b>COLOURS</b>	Charcoal Plum
<b>FRAME</b>	ALUXX-grade aluminum, 12x142mm thru-axle, flat mount disc, flip chip - dropout
<b>FORK</b>	Advanced-grade composite, full-composite OverDrive steerer, 12mm thru-axle, flat mount disc
<b>SHOCK</b>	N/A
COMPONENTS	
<b>HANDLEBAR</b>	Giant Contact XR D-Fuse, 31.8mm, 5-degree back sweep, flare drop, alloy XS: 400mm, S: 400mm, M: 420mm, L: 420mm
<b>GRIPS</b>	cork tape with gel
<b>STEM</b>	Giant Contact, +/- 8 degree, alloy XS: 50mm, S: 60mm, M: 70mm, L: 80mm
<b>SEATPOST</b>	Giant Contact D-Fuse, alloy, 14mm offset
<b>SADDLE</b>	Liv Approach
<b>PEDALS</b>	N/A
DRIVETRAIN	
<b>SHIFTERS</b>	Shimano GRX RX-400, 2x10
<b>FRONT DERAILLEUR</b>	Shimano Tiagra
<b>REAR DERAILLEUR</b>	Shimano GRX RX-400
<b>BRAKES</b>	Shimano GRX RX-400 hydraulic, Giant MPH rotors [F]160mm, [R]160mm
<b>BRAKE LEVERS</b>	Shimano GRX RX-400 hydraulic
<b>CASSETTE</b>	Shimano HG500, 11x34
<b>CHAIN</b>	KMC X10 with Missing Link
<b>CRANKSET</b>	FSA Omega Adventure, 32/48 XS: 165mm, S: 170mm, M: 172.5mm, L: 172.5mm
<b>BOTTOM BRACKET</b>	FSA Mega EXA

WHEELS	
<b>RIMS</b>	Giant S-X2 Disc wheelsset, alloy
<b>HUBS</b>	Giant alloy, 12mm thru-axle
<b>SPOKES</b>	stainless
<b>TIRES</b>	Giant CrossCut AT 2, 700x38c, tubeless
<b>EXTRAS</b>	53mm max tire size in long flip chip position, 45mm max tire size in short flip chip position, tubeless prepared, ISC clamp

**Price: \$2,499.00**

## GEOMETRY

FRAME	XS		S		M		L	
	SHORT	LONG	SHORT	LONG	SHORT	LONG	SHORT	LONG
Seat Tube Length (mm)	390	420	465	500				
Seat Tube Angle	74.5°   74.4°	74.5°   74.4°	74.5°   74.4°	74.5°   74.4°				
Top Tube Length (mm)	525   525	535   535	545   545	555   555				
Head Tube Length (mm)	90	110	140	160				
Head Tube Angle	70.0°   69.9°	70.5°   70.4°	71.0°   70.9°	71.0°   70.9°				
Fork Rake (mm)	50	50	50	50				
Trail (mm)	78.4   82	75   78.5	71.6   75.1	71.6   75				
Wheelbase (mm)	1017   1027	1024   1034	1031   1041	1043   1052				
Chain Stay Length (mm)	430   440	430   440	430   440	430   440				
Bottom Bracket Drop (mm)	80   81	80   81	80   81	80   81				
Stack (mm)	523   524	544   545	574   575	593   594				
Reach (mm)	380   379	384   383	386   385	391   389				
Stand Over Height (mm)	681   688	708   715	748   755	779   786				
Stem Length (mm)	50	60	70	80				
Crank Length (mm)	165	170	172.5	172.5				
Wheel Size	700	700	700	700				

Please note that our specifications may be impacted by running substitution changes, we highly recommend confirming the specifications of our products with your local retailer at the time of sale if purchasing in-store. \*Recommended Retail Prices are subject to change without notice and may vary from store to store depending on freight and assembly costs.