

DEVOTE 1



SPECS

FRAME	
SIZES	XS, S, M, L
COLORS	Dune Beige
FRAME	ALUXX-grade aluminum, 12x142mm thru-axle, flat mount disc, flip chip – dropout
FORK	Advanced-grade composite, full-composite OverDrive steerer, 12mm thru-axle, flat mount disc
SHOCK	N/A
COMPONENTS	
HANDLEBAR	Giant Contact XR D-Fuse, 31.8mm, 5-degree back sweep, flare drop, XS: 400mm, S: 400mm, M: 420mm, L: 420mm
GRIPS	Cork Tape w/ Gel VLT004-02
STEM	Giant Contact, 8-degree, XS: 50mm, S: 60mm, M: 70mm, L: 80mm
SEATPOST	Giant D-Fuse, alloy
SADDLE	Liv Grit
DRIVETRAIN	
SHIFTERS	Shimano CUES U6030, 2x10
FRONT DERAILLEUR	Shimano CUES U6030
REAR DERAILLEUR	Shimano CUES U6020
BRAKES	Shimano CUES BR-U6030 hydraulic, Giant MPH rotors, [F]160mm, [R]160mm
BRAKE LEVERS	Shimano CUES BR-U6030 hydraulic
CASSETTE	Shimano CS-LG300, 11x39
CHAIN	KMC X11 with Missing Link
CRANKSET	Shimano FC-U6030, 32/46, XS: 165mm, S: 170mm, M: 172.5mm, L: 172.5mm
BOTTOM BRACKET	Shimano, press fit

WHEELS	
RIMS	Giant S-X2 Disc, alloy
HUBS	Giant alloy, 12mm thru-axle
SPOKES	stainless steel
TIRES	CrossCut GRIP 1; 700x45c
EXTRAS	53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position, tubeless prepared, ISC clamp
LIMITS	
MAX TIRE CLEARANCE	53mm

Price: ₹ 1,849.00

GEOMETRY

FRAME	XS		S		M		L	
	SHORT	LONG	SHORT	LONG	SHORT	LONG	SHORT	LONG
Seat Tube Length (mm)	390	420	465	500				
Seat Tube Angle	74.5° 74.4°	74.5° 74.4°	74.5° 74.4°	74.5° 74.4°				
Top Tube Length (mm)	525 525	535 535	545 545	555 555				
Head Tube Length (mm)	90	110	140	160				
Head Tube Angle	70.0° 69.9°	70.5° 70.4°	71.0° 70.9°	71.0° 70.9°				
Fork Rake (mm)	50	50	50	50				
Trail (mm)	78.4 82	75 78.5	71.6 75.1	71.6 75				
Wheelbase (mm)	1017 1027	1024 1034	1031 1041	1043 1052				
Chain Stay Length (mm)	430 440	430 440	430 440	430 440				
Bottom Bracket Drop (mm)	80 81	80 81	80 81	80 81				
Stack (mm)	523 524	544 545	574 575	593 594				
Reach (mm)	380 379	384 383	386 385	391 389				
Stand Over Height (mm)	681 688	708 715	748 755	779 786				
Handlebar Width (mm)	400	400	420	420				
Stem Length (mm)	50	60	70	80				
Crank Length (mm)	165	170	172.5	172.5				

The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city / country.