

DEVOTE 1



ESPECIFICACIONES

| CUADRO | |
|----------------------|---|
| TALLAS | XS, S, M, L |
| COLORES | Dune Beige |
| CUADRO | ALUXX-grade aluminum, 12x142mm thru-axle, flat mount disc, flip chip – dropout |
| HORQUILLA | Advanced-grade composite, full-composite OverDrive steerer, 12mm thru-axle, flat mount disc |
| AMORTIGUADOR | N/A |
| COMPONENTES | |
| MANILLAR | Giant Contact XR D-Fuse, 31.8mm, 5-degree back sweep, flare drop, XS: 400mm, S: 400mm, M: 420mm, L: 420mm |
| PUÑOS | Cork Tape w/ Gel VLT004-02 |
| POTENCIA | Giant Contact, 8-degree, XS: 50mm, S: 60mm, M: 70mm, L: 80mm |
| TIJA DE SILLÍN | Giant D-Fuse, alloy |
| SILLÍN | Liv Grit |
| TRANSMISIÓN | |
| MANETAS DE CAMBIO | Shimano CUES U6030, 2x10 |
| DESVIADOR | Shimano CUES U6030 |
| CAMBIO TRASERO | Shimano CUES U6020 |
| FRENOS | Shimano CUES BR-U6030 hydraulic, Giant MPH rotors, [F]160mm, [R]160mm |
| PALANCAS DE FRENOS | Shimano CUES BR-U6030 hydraulic |
| CASSETTE | Shimano CS-LG300, 11x39 |
| CADENA | KMC X11 with Missing Link |
| JGO. PLATOS Y BIELAS | Shimano FC-U6030, 32/46, XS: 165mm, S: 170mm, M: 172.5mm, L: 172.5mm |
| CAJA DE PEDALIER | Shimano, press fit |

| RUEDAS | |
|-----------------------------|---|
| LLANTAS | Giant S-X2 Disc, alloy |
| BUJES | Giant alloy, 12mm thru-axle |
| RADIOS | stainless steel |
| CUBIERTAS | CrossCut GRIP 1; 700x45c |
| EXTRAS | 53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position, tubeless prepared, ISC clamp |
| LÍMITES | |
| MÁXIMA ANCHURA DE NEUMÁTICO | 53mm |

Precio: 1.849,00 €

GEOMETRÍA

| CUADRO | XS | | S | | M | |
|--|---------------|---------------|---------------|------|-------|------|
| | SHORT | LONG | SHORT | LONG | SHORT | LONG |
| Longitud del tubo del sillín (mm) | 390 | 420 | 465 | | | |
| Ángulo del tubo del sillín | 74,5° 74,4° | 74,5° 74,4° | 74,5° 74,4° | | | |
| Longitud del tubo superior (mm) (mm) | 525 525 | 535 535 | 545 545 | | | |
| Longitud del tubo de dirección (mm) (mm) | 90 | 110 | 140 | | | |
| Ángulo del tubo de dirección | 70,0° 69,9° | 70,5° 70,4° | 71,0° 70,9° | | | |
| Inclinación de la horquilla (mm) | 50 | 50 | 50 | | | |
| Trail (mm) (mm) | 78,4 82 | 75 78,5 | 71,6 75,1 | | | |
| Distancia entre ejes (mm) (mm) | 1017 1027 | 1024 1034 | 1031 1041 | | | |
| Longitud de la vaina (mm) (mm) | 430 440 | 430 440 | 430 440 | | | |
| Caída del eje de pedalier (mm) (mm) | 80 81 | 80 81 | 80 81 | | | |
| Stack (mm) (mm) | 523 524 | 544 545 | 574 575 | | | |
| Reach (mm) (mm) | 380 379 | 384 383 | 386 385 | | | |
| Altura del suelo al tubo (mm) (mm) | 681 688 | 708 715 | 748 755 | | | |
| Ancho del manillar (mm) (mm) | 400 | 400 | 420 | | | |
| Longitud de la potencia (mm) (mm) | 50 | 60 | 70 | | | |
| Longitud de las bielas (mm) (mm) | 165 | 170 | 172,5 | | | |

Giant se reserva el derecho a modificar especificaciones, precios o colores sin previo aviso.