

# DEVOTE 1



## TEKNISET TIEDOT

RUNKO	
KOOT	XS, S, M, L
VÄRIT	Dune Beige
RUNKO	ALUXX-grade aluminum, 12x142mm thru-axle, flat mount disc, flip chip – dropout
HAARUKKA	Advanced-grade composite, full-composite OverDrive steerer, 12mm thru-axle, flat mount disc
ISKUNVAIMENNIN	N/A
KOMPONENTIT	
OHJAUSTANKO	Giant Contact XR D-Fuse, 31.8mm, 5-degree back sweep, flare drop, XS: 400mm, S: 400mm, M: 420mm, L: 420mm
GRIPIT	Cork Tape w/ Gel VLT004-02
OHJAINKANNATIN	Giant Contact, 8-degree, XS: 50mm, S: 60mm, M: 70mm, L: 80mm
SATULATOLPPA	Giant D-Fuse, alloy
SATULA	Liv Grit
VOIMANSIIRTO	
VAIHDEVIPU	Shimano CUES U6030, 2x10
ETUVAIHTAJA	Shimano CUES U6030
TAKAVAIHTAJA	Shimano CUES U6020
JARRUT	Shimano CUES BR-U6030 hydraulic, Giant MPH rotors, [F]160mm, [R]160mm
JARRUKAHVAT	Shimano CUES BR-U6030 hydraulic
RATASPAKKA	Shimano CS-LG300, 11x39
KETJUT	KMC X11 with Missing Link
KAMPISARJA	Shimano FC-U6030, 32/46, XS: 165mm, S: 170mm, M: 172.5mm, L: 172.5mm
KESKIÖ	Shimano, press fit

RENKAAT	
VANTEET	Giant S-X2 Disc, alloy
NAVAT	Giant alloy, 12mm thru-axle
PINNAT	stainless steel
RENKAAT	CrossCut GRIP 1; 700x45c
LISÄTIEDOT	53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position, tubeless prepared, ISC clamp
RAJOITTEET	
MAX RENGASVARA	53mm

Suositusuhinta: 1 899,00 €

## GEOMETRIA

RUNKO	XS		S		M		L	
	SHORT	LONG	SHORT	LONG	SHORT	LONG	SHORT	LONG
Satulaputken pituus (mm)	390	420	465	500				
Satulaputken kulma	74,5°   74,4°	74,5°   74,4°	74,5°   74,4°	74,5°   74,4°	74,5°   74,4°			
Vaakaputken pituus (mm)	525   525	535   535	545   545	555   555				
Emäputken pituus (mm)	90	110	140	160				
Emäputken kulma	70,0°   69,9°	70,5°   70,4°	71,0°   70,9°	71,0°   70,9°				
Haarukan offset (mm)	50	50	50	50				
Trail-mitta (mm)	78,4   82	75   78,5	71,6   75,1	71,6   75				
Akseliväli (mm)	1017   1027	1024   1034	1031   1041	1043   1052				
Takahaarukan alaputken pituus (mm)	430   440	430   440	430   440	430   440				
Keskiön pudotus (mm)	80   81	80   81	80   81	80   81				
Stack-mitta (mm)	523   524	544   545	574   575	593   594				
Reach-mitta (mm)	380   379	384   383	386   385	391   389				
Standover-mitta (mm)	681   688	708   715	748   755	779   786				
Ohjaustangon leveys (mm)	400	400	420	420				
Ohjainkannattimen pituus (mm)	50	60	70	80				
Kammen pituus (mm)	165	170	172,5	172,5				

Kaikki ilmoitetut tekniset tiedot voivat muuttua ilman erillistä ilmoitusta.