

# DEVOTE 1



## SPECIFICATIES

FRAME	
MATEN	XS, S, M, L
KLEUREN	Dune Beige
FRAME	ALUXX-grade aluminum, 12x142mm thru-axle, flat mount disc, flip chip – dropout
VOORVORK	Advanced-grade composite, full-composite OverDrive steerer, 12mm thru-axle, flat mount disc
DEMPER	N/A
ONDERDELEN	
STUUR	Giant Contact XR D-Fuse, 31.8mm, 5-degree back sweep, flare drop, XS: 400mm, S: 400mm, M: 420mm, L: 420mm
HANDVATTEN	Cork Tape w/ Gel VLT004-02
STUURPEN	Giant Contact, 8-degree, XS: 50mm, S: 60mm, M: 70mm, L: 80mm
ZADELPEN	Giant D-Fuse, alloy
ZADEL	Liv Grit
AFMONTAGE	
SHIFTERS	Shimano CUES U6030, 2x10
VOORDERAILLEUR	Shimano CUES U6030
ACHTERDERAILLEUR	Shimano CUES U6020
REMMEN	Shimano CUES BR-U6030 hydraulic, Giant MPH rotors, [F]160mm, [R]160mm
REMHENDELS	Shimano CUES BR-U6030 hydraulic
CASSETTE	Shimano CS-LG300, 11x39
AANDRIJVING	KMC X11 with Missing Link
CRANKSET	Shimano FC-U6030, 32/46, XS: 165mm, S: 170mm, M: 172.5mm, L: 172.5mm
BOTTOM BRACKET	Shimano, press fit

WIELSET	
VELGEN	Giant S-X2 Disc, alloy
NAVEN	Giant alloy, 12mm thru-axle
SPAKEN	stainless steel
BANDEN	CrossCut GRIP 1; 700x45c
EXTRA'S	53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position, tubeless prepared, ISC clamp
LIMITS	
MAXIMALE BANDENVIJHEID	53mm

Adviesprijs: € 1.749,00

## GEOMETRIE

FRAME	XS		S		M		L	
	SHORT	LONG	SHORT	LONG	SHORT	LONG	SHORT	LONG
Zitbuis Lengte (mm)	390	420	465	500				
Zitbuis Hoek	74,5°   74,4°	74,5°   74,4°	74,5°   74,4°	74,5°   74,4°				
Frame Lengte (horizontaal) (mm)	525   525	535   535	545   545	555   555				
Balhoofdbuis Lengte (mm)	90	110	140	160				
Balhoofdbuis Hoek	70,0°   69,9°	70,5°   70,4°	71,0°   70,9°	71,0°   70,9°				
Vork Sprong (mm)	50	50	50	50				
Naloop (mm)	78,4   82	75   78,5	71,6   75,1	71,6   75				
Wielbasis (mm)	1017   1027	1024   1034	1031   1041	1043   1052				
Liggende achtervork lengte (mm)	430   440	430   440	430   440	430   440				
Bottom Bracket Drop (mm)	80   81	80   81	80   81	80   81				
Stack (mm)	523   524	544   545	574   575	593   594				
Reach (mm)	380   379	384   383	386   385	391   389				
Stand Over Height (mm)	681   688	708   715	748   755	779   786				
Stuur breedte (mm)	400	400	420	420				
Stuurpen Lengte (mm)	50	60	70	80				
Cranklengte (mm)	165	170	172,5	172,5				

Deze specificaties zijn met de grootste zorgvuldigheid samengesteld. Specificaties, beschikbaarheid, prijzen en kleuren kunnen echter zonder voor aankondiging wijzigen.