

# DEVOTE 1



## SPECIFICATIES

| FRAME            |                                                                                                           |
|------------------|-----------------------------------------------------------------------------------------------------------|
| MATEN            | XS, S, M, L                                                                                               |
| KLEUREN          | Dune Beige                                                                                                |
| FRAME            | ALUXX-grade aluminum, 12x142mm thru-axle, flat mount disc, flip chip – dropout                            |
| VOORVORK         | Advanced-grade composite, full-composite OverDrive steerer, 12mm thru-axle, flat mount disc               |
| DEMPER           | N/A                                                                                                       |
| ONDERDELEN       |                                                                                                           |
| STUUR            | Giant Contact XR D-Fuse, 31.8mm, 5-degree back sweep, flare drop, XS: 400mm, S: 400mm, M: 420mm, L: 420mm |
| HANDVATTEN       | Cork Tape w/ Gel VLT004-02                                                                                |
| STUURPEN         | Giant Contact, 8-degree, XS: 50mm, S: 60mm, M: 70mm, L: 80mm                                              |
| ZADELPEN         | Giant D-Fuse, alloy                                                                                       |
| ZADEL            | Liv Grit                                                                                                  |
| AFMONTAGE        |                                                                                                           |
| SHIFTERS         | Shimano CUES U6030, 2x10                                                                                  |
| VOORDERAILLEUR   | Shimano CUES U6030                                                                                        |
| ACHTERDERAILLEUR | Shimano CUES U6020                                                                                        |
| REMMEN           | Shimano CUES BR-U6030 hydraulic, Giant MPH rotors, [F]160mm, [R]160mm                                     |
| REMHENDELS       | Shimano CUES BR-U6030 hydraulic                                                                           |
| CASSETTE         | Shimano CS-LG300, 11x39                                                                                   |
| AANDRIJVING      | KMC X11 with Missing Link                                                                                 |
| CRANKSET         | Shimano FC-U6030, 32/46, XS: 165mm, S: 170mm, M: 172.5mm, L: 172.5mm                                      |
| BOTTOM BRACKET   | Shimano, press fit                                                                                        |

| WIELSET                 |                                                                                                                                 |
|-------------------------|---------------------------------------------------------------------------------------------------------------------------------|
| VELGEN                  | Giant S-X2 Disc, alloy                                                                                                          |
| NAVEN                   | Giant alloy, 12mm thru-axle                                                                                                     |
| SPAKEN                  | stainless steel                                                                                                                 |
| BANDEN                  | CrossCut GRIP 1; 700x45c                                                                                                        |
| EXTRA'S                 | 53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position, tubeless prepared, ISC clamp |
| LIMITS                  |                                                                                                                                 |
| MAXIMALE BANDENVRIJHEID | 53mm                                                                                                                            |

Adviesprijs: € 1.749,00

## GEOMETRIE

| FRAME                           | XS            | S             | M             | L             |
|---------------------------------|---------------|---------------|---------------|---------------|
|                                 | SHORT   LONG  | SHORT   LONG  | SHORT   LONG  | SHORT   LONG  |
| Zitbuis Lengte (mm)             | 390           | 420           | 465           | 500           |
| Zitbuis Hoek                    | 74,5°   74,4° | 74,5°   74,4° | 74,5°   74,4° | 74,5°   74,4° |
| Frame Lengte (horizontaal) (mm) | 525   525     | 535   535     | 545   545     | 555   555     |
| Balhoofdbuis Lengte (mm)        | 90            | 110           | 140           | 160           |
| Balhoofdbuis Hoek               | 70,0°   69,9° | 70,5°   70,4° | 71,0°   70,9° | 71,0°   70,9° |
| Vork Sprong (mm)                | 50            | 50            | 50            | 50            |
| Naloop (mm)                     | 78,4   82     | 75   78,5     | 71,6   75,1   | 71,6   75     |
| Wielbasis (mm)                  | 1017   1027   | 1024   1034   | 1031   1041   | 1043   1052   |
| Liggende achtervork lengte (mm) | 430   440     | 430   440     | 430   440     | 430   440     |
| Bottom Bracket Drop (mm)        | 80   81       | 80   81       | 80   81       | 80   81       |
| Stack (mm)                      | 523   524     | 544   545     | 574   575     | 593   594     |
| Reach (mm)                      | 380   379     | 384   383     | 386   385     | 391   389     |
| Stand Over Height (mm)          | 681   688     | 708   715     | 748   755     | 779   786     |
| Stuur breedte (mm)              | 400           | 400           | 420           | 420           |
| Stuurpen Lengte (mm)            | 50            | 60            | 70            | 80            |
| Cranklengte (mm)                | 165           | 170           | 172,5         | 172,5         |

Deze specificaties zijn met de grootste zorgvuldigheid samengesteld. Specificaties, beschikbaarheid, prijzen en kleuren kunnen echter zonder voor aankondiging wijzigen.