

DEVOTE 1



SPECIFICATIES

FRAME	
MATEN	XS, S, M, L
KLEUREN	Grayish Blue
FRAME	ALUXX-Grade Aluminum, 12x142mm thru-axle, disc
VOORVORK	Advanced-Grade Composite, full-composite OverDrive steerer, 12mm thru-axle, disc
DEMPER	N/A
ONDERDELEN	
STUUR	Giant Contact XR D-Fuse, 31.8 XS:40cm, S:40cm, M:42cm, L:42cm
HANDVATTEN	Liv All Condition
STUURPEN	Giant Contact XS:70mm, S:80mm, M:90mm, L:90mm
ZADEL	Liv Approach
PEDALEN	no pedal [GA, Pan-Eu]platform pedal [GU, GV, G]pedal w/toeclip and strap [All other GSC]
AFMONTAGE	
SHIFTERS	Shimano GRX RX-400, 2x10
VOORDERAILLEUR	Shimano Tiagra
ACHTERDERAILLEUR	Shimano GRX RX-400
REMMEN	Shimano GRX RX-400 hydraulic, Giant MPH rotors [F]160mm, [R]160mm
REMHENDELS	Shimano GRX RX-400 hydraulic
CASSETTE	Shimano HG500, 11x34
AANDRIJVING	KMC X10 with Missing Link
CRANKSET	FSA Omega Adventure, 32/48 XS:165mm, S:170mm, M:172.5mm, L:172.5mm
BOTTOM BRACKET	FSA Mega EXA, press fit

WIELSET	
VELGEN	Giant S-X2 Disc wheelset
NAVEN	Giant S-X2 Disc wheelset
SPAKEN	Giant S-X2 Disc wheelset
BANDEN	Giant CrossCut AT 2, 700x38c, tubeless
EXTRA'S	tubeless prepared, 45mm max tire size

Adviesprijs: € 1.699,00

GEOMETRIE

FRAME	XS	S	M	L
Zitbuis lengte (mm)	390	420	465	500
Zitbuis hoek	75,0°	75,0°	74,5°	74,5°
Frame Lengte (horizontaal) (mm)	515	525	535	550
Balhoofdbuis Lengte (mm)	95	125	155	180
Balhoofdbuis Hoek	70,5°	70,5°	71,0°	71,0°
Vork Sprong (mm)	50	50	50	50
Naloop (mm)	75,9	75,9	72,5	72,5
Wielbasis (mm)	1013	1020	1022	1039
Liggende achtervork lengte (mm)	430	430	430	430
Bottom Bracket Drop (mm)	80	80	80	80
Stack (mm)	530	558	588	612
Reach (mm)	378	376	372	380
ReachToHandlebar (mm)	429	437	443	452
Stand Over Height (mm)	678	706	744	774
Stuur breedte (mm)	400	400	420	420
Stuurpen Lengte (mm)	70	80	90	90
Cranklengte (mm)	165	170	172,5	172,5
Wielmaat	700c	700c	700c	700c

Deze specificaties zijn met de grootste zorgvuldigheid samengesteld. Specificaties, beschikbaarheid, prijzen en kleuren kunnen echter zonder voorafkondiging wijzigen.