

DEVOTE 1



SPECIFICATIES

FRAME	
MATEN	XS, S, M, L
KLEUREN	Dune Beige
FRAME	ALUXX-grade aluminum, 12x142mm thru-axle, flat mount disc, flip chip – dropout
VOORVORK	Advanced-grade composite, full-composite OverDrive steerer, 12mm thru-axle, flat mount disc
DEMPER	N/A
ONDERDELEN	
STUUR	Giant Contact XR D-Fuse, 31.8mm, 5-degree back sweep, flare drop, XS: 400mm, S: 400mm, M: 420mm, L: 420mm
HANDVATTEN	Cork Tape w/ Gel VLT004-02
STUURPEN	Giant Contact, 8-degree, XS: 50mm, S: 60mm, M: 70mm, L: 80mm
ZADEL	Giant D-Fuse, alloy
ZADEL	Liv Grit
AFMONTAGE	
SHIFTERS	Shimano CUES U6030, 2x10
VOORDERAILLEUR	Shimano CUES U6030
ACHTERDERAILLEUR	Shimano CUES U6020
REMMEN	Shimano CUES BR-U6030 hydraulic, Giant MPH rotors, [F]160mm, [R]160mm
REMHENDELS	Shimano CUES BR-U6030 hydraulic
CASSETTE	Shimano CS-LG300, 11x39
AANDRIJVING	KMC X11 with Missing Link
CRANKSET	Shimano FC-U6030, 32/46, XS: 165mm, S: 170mm, M: 172.5mm, L: 172.5mm
BOTTOM BRACKET	Shimano, press fit

WIELSET	
VELGEN	Giant S-X2 Disc, alloy
NAVEN	Giant alloy, 12mm thru-axle
SPAKEN	stainless steel
BANDEN	CrossCut GRIP 1; 700x45c
EXTRA'S	53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position, tubeless prepared, ISC clamp
LIMITS	
MAX TIRE CLEARANCE	53mm

Adviesprijs: € 1.749,00

GEOMETRIE

FRAME	XS	S	M	L
	SHORT LONG	SHORT LONG	SHORT LONG	SHORT LONG
Zitbuis lengte (mm)	390	420	465	500
Zitbuis hoek	74,5° 74,4°	74,5° 74,4°	74,5° 74,4°	74,5° 74,4°
Frame Lengte (horizontaal) (mm)	525 525	535 535	545 545	555 555
Balhoofdbuis Lengte (mm)	90	110	140	160
Balhoofdbuis Hoek	70,0° 69,9°	70,5° 70,4°	71,0° 70,9°	71,0° 70,9°
Vork Sprong (mm)	50	50	50	50
Naloop (mm)	78,4 82	75 78,5	71,6 75,1	71,6 75
Wielbasis (mm)	1017 1027	1024 1034	1031 1041	1043 1052
Liggende achtervork lengte (mm)	430 440	430 440	430 440	430 440
Bottom Bracket Drop (mm)	80 81	80 81	80 81	80 81
Stack (mm)	523 524	544 545	574 575	593 594
Reach (mm)	380 379	384 383	386 385	391 389
Stand Over Height (mm)	681 688	708 715	748 755	779 786
Stuur breedte (mm)	400	400	420	420
Stuurpen Lengte (mm)	50	60	70	80
Cranklengte (mm)	165	170	172,5	172,5

Deze specificaties zijn met de grootste zorgvuldigheid samengesteld. Specificaties, beschikbaarheid, prijzen en kleuren kunnen echter zonder voorafkondiging wijzigen.