

DEVOTE 1



SPECS

| CADRU | |
|-----------------------------------|---|
| MARIMI | XS, S, M, L |
| CULORI | Dune Beige |
| CADRU | ALUXX-grade aluminum, 12x142mm thru-axle, flat mount disc, flip chip – dropout |
| FURCA | Advanced-grade composite, full-composite OverDrive steerer, 12mm thru-axle, flat mount disc |
| SOC | N/A |
| COMPONENTE | |
| GHIDON | Giant Contact XR D-Fuse, 31.8mm, 5-degree back sweep, flare drop, XS: 400mm, S: 400mm, M: 420mm, L: 420mm |
| GRIPS | Cork Tape w/ Gel VLT004-02 |
| PIPA | Giant Contact, 8-degree, XS: 50mm, S: 60mm, M: 70mm, L: 80mm |
| TIJA SA | Giant D-Fuse, alloy |
| SA | Liv Grit |
| SISTEMUL DE SCHIMBARE A VITEZELOR | |
| MANETE SCHIMBATOR | Shimano CUES U6030, 2x10 |
| SCHIMBATOR FATA | Shimano CUES U6030 |
| SCHIMBATOR SPATE | Shimano CUES U6020 |
| FRANE | Shimano CUES BR-U6030 hydraulic, Giant MPH rotors, [F]160mm, [R]160mm |
| MANETE FRANA | Shimano CUES BR-U6030 hydraulic |
| PINIOANE | Shimano CS-LG300, 11x39 |
| LANT | KMC X11 with Missing Link |
| ANGRENAJ | Shimano FC-U6030, 32/46, XS: 165mm, S: 170mm, M: 172.5mm, L: 172.5mm |
| BOTTOM BRACKET | Shimano, press fit |

| ROTI | |
|--------------------|---|
| JANTE | Giant S-X2 Disc, alloy |
| BUTUCI | Giant alloy, 12mm thru-axle |
| SPITE | stainless steel |
| ANVELOPE | CrossCut GRIP 1; 700x45c |
| EXTRAS | 53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position, tubeless prepared, ISC clamp |
| LIMITS | |
| MAX TIRE CLEARANCE | 53mm |

GEOMETRIE

| CADRU | XS | S | M | L |
|--------------------------|---------------|---------------|---------------|---------------|
| | SHORT LONG | SHORT LONG | SHORT LONG | SHORT LONG |
| Seat Tube Length (mm) | 390 | 420 | 465 | 500 |
| Seat Tube Angle | 74,5° 74,4° | 74,5° 74,4° | 74,5° 74,4° | 74,5° 74,4° |
| Top Tube Length (mm) | 525 525 | 535 535 | 545 545 | 555 555 |
| Head Tube Length (mm) | 90 | 110 | 140 | 160 |
| Head Tube Angle | 70,0° 69,9° | 70,5° 70,4° | 71,0° 70,9° | 71,0° 70,9° |
| Fork Rake (mm) | 50 | 50 | 50 | 50 |
| Trail (mm) | 78,4 82 | 75 78,5 | 71,6 75,1 | 71,6 75 |
| Wheelbase (mm) | 1017 1027 | 1024 1034 | 1031 1041 | 1043 1052 |
| Chain Stay Length (mm) | 430 440 | 430 440 | 430 440 | 430 440 |
| Bottom Bracket Drop (mm) | 80 81 | 80 81 | 80 81 | 80 81 |
| Stack (mm) | 523 524 | 544 545 | 574 575 | 593 594 |
| Reach (mm) | 380 379 | 384 383 | 386 385 | 391 389 |
| Stand Over Height (mm) | 681 688 | 708 715 | 748 755 | 779 786 |
| Handlebar Width (mm) | 400 | 400 | 420 | 420 |
| Stem Length (mm) | 50 | 60 | 70 | 80 |
| Crank Length (mm) | 165 | 170 | 172,5 | 172,5 |

Toate specificatiile enumerate se pot schimba fara notificare prealabila.