

# DEVOTE 1



## SPECIFIKACIJE

OKVIR	
VELIKOSTI	XS, S, M, L
BARVE	Dune Beige
OKVIR	ALUXX-grade aluminum, 12x142mm thru-axle, flat mount disc, flip chip – dropout
VILICE	Advanced-grade composite, full-composite OverDrive steerer, 12mm thru-axle, flat mount disc
AMORTIZER	N/A
KOMPONENTE	
KRMILO	Giant Contact XR D-Fuse, 31.8mm, 5-degree back sweep, flare drop, XS: 400mm, S: 400mm, M: 420mm, L: 420mm
GRIPS	Cork Tape w/ Gel VLT004-02
OPORA KRMILA	Giant Contact, 8-degree, XS: 50mm, S: 60mm, M: 70mm, L: 80mm
OPORA SEDEŽA	Giant D-Fuse, alloy
SEDEŽ	Liv Grit
POGON	
PRESTAVNE ROČICE	Shimano CUES U6030, 2x10
PREDNJI MENJALNIK	Shimano CUES U6030
ZADNJI MENJALNIK	Shimano CUES U6020
ZAVORE	Shimano CUES BR-U6030 hydraulic, Giant MPH rotors, [F]160mm, [R]160mm
ZAVORNE ROČICE	Shimano CUES BR-U6030 hydraulic
VERIŽNIK	Shimano CS-LG300, 11x39
VERIGA	KMC X11 with Missing Link
GONILKE Z VERIŽNIKI	Shimano FC-U6030, 32/46, XS: 165mm, S: 170mm, M: 172.5mm, L: 172.5mm
BOTTOM BRACKET	Shimano, press fit

OBROČNIKI	
OBROČI	Giant S-X2 Disc, alloy
PESTA	Giant alloy, 12mm thru-axle
NAPERE	stainless steel
PLAŠČI	CrossCut GRIP 1; 700x45c
DODATKI	53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position, tubeless prepared, ISC clamp
LIMITS	
MAX TIRE CLEARANCE	53mm

## GEOMETRIJA

OKVIR	XS	S	M	L
	SHORT   LONG SHORT   LONG SHORT   LONG SHORT   LONG			
Dolžina sedežne cevi (mm)	390	420	465	500
Kot sedežne cevi	74,5°   74,4°	74,5°   74,4°	74,5°   74,4°	74,5°   74,4°
Top Tube Length (mm)	525   525	535   535	545   545	555   555
Višina glave okvirja (mm)	90	110	140	160
Krmilni kot	70,0°   69,9°	70,5°   70,4°	71,0°   70,9°	71,0°   70,9°
Zamik vpetja osi (mm)	50	50	50	50
Trail (mm)	78,4   82	75   78,5	71,6   75,1	71,6   75
Medosna razdalja (mm)	1017   1027	1024   1034	1031   1041	1043   1052
Dolžina cevi ob verigi (mm)	430   440	430   440	430   440	430   440
Bottom Bracket Drop (mm)	80   81	80   81	80   81	80   81
Oddaljenost zgornje cevi od gonilne osi (mm)	523   524	544   545	574   575	593   594
Doseg (mm)	380   379	384   383	386   385	391   389
Višina zgornje cevi (mm)	681   688	708   715	748   755	779   786
Širina krmila (mm)	400	400	420	420
Dolžina opore krmila (mm)	50	60	70	80
Dolžina gonilke (mm)	165	170	172,5	172,5

Vse navedene specifikacije se lahko spremenijo brez obvestila.