

# DEVOTE 1



## SPECS

RAM	
STORLEKAR	XS, S, M, L
FÄRGER	Dune Beige
RAM	ALUXX-grade aluminum, 12x142mm thru-axle, flat mount disc, flip chip – dropout
GAFFEL	Advanced-grade composite, full-composite OverDrive steerer, 12mm thru-axle, flat mount disc
BAKDÄMPARE	N/A
KOMPONENTER	
STYRE	Giant Contact XR D-Fuse, 31.8mm, 5-degree back sweep, flare drop, XS: 400mm, S: 400mm, M: 420mm, L: 420mm
GREPPAR	Cork Tape w/ Gel VLT004-02
STAM	Giant Contact, 8-degree, XS: 50mm, S: 60mm, M: 70mm, L: 80mm
SADELSTOLPE	Giant D-Fuse, alloy
SADEL	Liv Grit
DRIVLINA	
VÄXLAR	Shimano CUES U6030, 2x10
FRAMVÄXEL	Shimano CUES U6030
BAKVÄXEL	Shimano CUES U6020
BROMSAR	Shimano CUES BR-U6030 hydraulic, Giant MPH rotors, [F]160mm, [R]160mm
BROMSSPAKAR	Shimano CUES BR-U6030 hydraulic
KASSETT	Shimano CS-LG300, 11x39
KEDJA	KMC X11 with Missing Link
VEVPARTI	Shimano FC-U6030, 32/46, XS: 165mm, S: 170mm, M: 172.5mm, L: 172.5mm
BROMSREGLAGE	Shimano, press fit

HJUL	
FÄLGAR	Giant S-X2 Disc, alloy
NAV	Giant alloy, 12mm thru-axle
EKRAR	stainless steel
DÄCK	CrossCut GRIP 1; 700x45c
EXTRAFUNKTIONER	53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position, tubeless prepared, ISC clamp
GRÄNSER	
MAX DÄCKAVSTÅND	53mm

Price: 20 990,00 kr

## GEOMETRY

RAM	XS		S		M		L	
	SHORT	LONG	SHORT	LONG	SHORT	LONG	SHORT	LONG
Längd sadelrör (mm)	390		420		465		500	
Vinkel sadelrör	74,5°   74,4°		74,5°   74,4°		74,5°   74,4°		74,5°   74,4°	
Topprörets längd (mm)	525   525		535   535		545   545		555   555	
Styrhuvud Längd (mm)	90		110		140		160	
Vinkel styrhuvud	70,0°   69,9°		70,5°   70,4°		71,0°   70,9°		71,0°   70,9°	
Gaffelvinkel (mm)	50		50		50		50	
Spår (mm)	78,4   82		75   78,5		71,6   75,1		71,6   75	
Hjulbas (mm)	1017   1027		1024   1034		1031   1041		1043   1052	
Kedjestagslängd (mm)	430   440		430   440		430   440		430   440	
Nedre fäste Drop (mm)	80   81		80   81		80   81		80   81	
Stack (mm)	523   524		544   545		574   575		593   594	
Reach (mm)	380   379		384   383		386   385		391   389	
Stå över höjden (mm)	681   688		708   715		748   755		779   786	
Styrets bredd (mm)	400		400		420		420	
Stamlängd (mm)	50		60		70		80	
Vevlängd (mm)	165		170		172,5		172,5	

All specifications listed are subject to change without notice.