

# DEVOTE 2



## SPECS

FRAME	
<b>SIZES</b>	XS, S, M, L
<b>COLORS</b>	Gleaming Olive
<b>FRAME</b>	ALUXX-grade aluminum, 12x142mm thru-axle, flat mount disc, flip chip – dropout
<b>FORK</b>	Advanced-grade composite, full-composite OverDrive steerer, 12mm thru-axle, flat mount disc
COMPONENTS	
<b>HANDLEBAR</b>	Giant Contact XR D-Fuse, 31.8mm, 5-degree back sweep, flare drop, XS: 400mm, S: 400mm, M: 420mm, L: 420mm
<b>GRIPS</b>	Cork Tape w/ Gel VLT004-02
<b>STEM</b>	Giant Contact, 8-degree, XS: 50mm, S: 60mm, M: 70mm, L: 80mm
<b>SEATPOST</b>	Giant D-Fuse, alloy
<b>SADDLE</b>	Liv Grit
DRIVETRAIN	
<b>SHIFTERS</b>	Shimano CUES U3030, 2x9
<b>FRONT DERAILLEUR</b>	Shimano CUES U6030
<b>REAR DERAILLEUR</b>	Shimano CUES U4020
<b>BRAKES</b>	Shimano Mechanical Disc Brake BR-RS305 SUPER SLR, [F]160mm, [R]160mm
<b>BRAKE LEVERS</b>	Shimano CUES BR-U3030 hydraulic
<b>CASSETTE</b>	Shimano CS-LG300, 11x36
<b>CHAIN</b>	KMC X11 with Missing Link
<b>CRANKSET</b>	Shimano FC-U6030, 32/46, XS: 165mm, S: 170mm, M: 172.5mm, L: 172.5mm
<b>BOTTOM BRACKET</b>	Shimano, press fit

WHEELS	
<b>RIMS</b>	Giant S-X2 Disc, alloy
<b>HUBS</b>	Giant alloy, 12mm thru-axle
<b>SPOKES</b>	stainless steel
<b>TIRES</b>	CrossCut GRIP 1; 700x45c
<b>EXTRAS</b>	53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position, tubeless prepared, ISC clamp
LIMITS	
<b>MAX TIRE CLEARANCE</b>	53mm

## GEOMETRY

FRAME	XS		S		M		L	
	SHORT	LONG	SHORT	LONG	SHORT	LONG	SHORT	LONG
Seat Tube Length (mm)	390		420		465		500	
Seat Tube Angle	74,5°	74,4°	74,5°	74,4°	74,5°	74,4°	74,5°	74,4°
Top Tube Length (mm)	525	525	535	535	545	545	555	555
Head Tube Length (mm)	90		110		140		160	
Head Tube Angle	70,0°	69,9°	70,5°	70,4°	71,0°	70,9°	71,0°	70,9°
Fork Rake (mm)	50		50		50		50	
Trail (mm)	78,4	82	75	78,5	71,6	75,1	71,6	75
Wheelbase (mm)	1017	1027	1024	1034	1031	1041	1043	1052
Chain Stay Length (mm)	430	440	430	440	430	440	430	440
Bottom Bracket Drop (mm)	80	81	80	81	80	81	80	81
Stack (mm)	523	524	544	545	574	575	593	594
Reach (mm)	380	379	384	383	386	385	391	389
Stand Over Height (mm)	681	688	708	715	748	755	779	786
Handlebar Width (mm)	400		400		420		420	
Stem Length (mm)	50		60		70		80	
Crank Length (mm)	165		170		172,5		172,5	

All specifications listed are subject to change without notice.