DEVOTE ADVANCED 0

СПЕЦИФИКАЦИИ

РАМКА	
РАЗМЕР	XS, S, M, L
ЦВЯТ	Camel Silk/Chrome
РАМКА	Advanced-grade composite, 12x142mm thru-axle, flat mount disc, flip chip – dropout, integrated down tube storage
ВИЛКА	Advanced-grade composite, full-composite OverDrive steerer, 12mm thru-axle, flat mount disc, FSA stainless upper/lower bearings
КОМПОНЕНТИ	
КОРМИЛО	Giant Contact XR D-Fuse, 31.8mm, 5-degree back sweep, flare drop, XS: 400mm, S: 400mm, M: 420mm, L: 420mm
ГРИПОВЕ	Liv All Condition
ЛАПА	Giant Contact AeroLight, -10-degree, XS: 50mm, S: 60mm, M: 70mm, L: 80mm
КОЛЧЕ ЗА СЕДАЛКА	Giant D-Fuse, composite, -5/+15mm offset
СЕДАЛКА	Liv Grit
DRIVETRAIN	
КОМАНДИ	Shimano GRX RX-820, 2x12
ПРЕДЕН ДЕРАЙЛЬОР	Shimano GRX RX-820
ЗАДЕН ДЕРАЙЛЬОР	Shimano GRX RX-820
СПИРАЧКИ	Shimano GRX RX-820 hydraulic, Shimano RT-70 rotors, [F]160mm, [R]160mm
РЪКОХВАТКИ ЗА СПИРАЧКИ	Shimano GRX RX-820 hydraulic
КАСЕТА	Shimano CS-HG710, 12-speed, 11x36
ВЕРИГА	KMC X12L-1
КУРБЕЛ	Shimano GRX RX-820, 31/48, XS: 165mm, S: 170mm, M: 172.5mm, L: 172.5mm
СРЕДНА КАСЕТА	Shimano, press fit

КАПЛИ	
ШИНИ	Giant CXR 2, [F] 35mm, [R] 35mm
ГЛАВИНИ	[F] Giant alloy, CenterLock, 12mm thru-axle, [R] Giant AR alloy, 3-pawl driver, 36t, CenterLock, 12mm thru-axle
СПИЦИ	Sapim Sprint
ГУМИ	Crosscut Grip 45c
ЕКСТРИ	53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position, tubeless prepared, ISC clamp, in-frame storage bag
ЛИМИТИ	
MAX TIRE CLEARANCE	53mm

ГЕОМЕТРИЯ

РАМКА	XS	S	M	L
	SHORT | LONG	SHORT | LONG	SHORT | LONG	SHORT | LONG
Seat Tube Length (mm)	390	420	465	500
Seat Tube Angle	74,5° | 74,4°	74,5° | 74,4°	74,5° | 74,4°	74,5° | 74,4°
Top Tube Length (mm)	525 | 525	535 | 535	545 | 545	555 | 555
Head Tube Length (mm)	90	110	140	160
Head Tube Angle	70,0° | 69,9°	70,5° | 70,4°	71,0° | 70,9°	71,0° | 70,9°
Fork Rake (mm)	50	50	50	50
Trail (mm)	78,4 | 82	75 | 78,5	71,6 | 75,1	71,6 | 75
Wheelbase (mm)	1012 | 1022	1019 | 1029	1026 | 1036	1043 | 1052
Chain Stay Length (mm)	425 | 435	425 | 435	425 | 435	430 | 440
Bottom Bracket Drop (mm)	80 | 81	80 | 81	80 | 81	80 | 81
Stack (mm)	523 | 524	544 | 545	574 | 575	593 | 594
Обсег (mm)	380 | 379	384 | 383	386 | 385	391 | 389
Stand Over Height (mm)	681 | 688	708 | 715	748 | 755	779 | 786
Ширина на Кормило (mm)	400	400	420	420
Дължина на Лапа (mm)	50	60	70	80
Дължина на Курбел (mm)	165	170	172,5	172,5

All specifications listed are subject to change without notice.