

DEVOTE ADVANCED 0



SPECIFIKACE

RÁM	
VELIKOSTI	S, M, L
BARVA	Tiger Red
RÁM	Advanced-grade composite, 12x142mm thru-axle, flat mount disc, flip chip – dropout, integrated down tube storage
VIDLICE	Advanced-grade composite, full-composite OverDrive steerer, 12mm thru-axle, flat mount disc, FSA stainless upper/lower bearings
TLUMIČ	-
KOMPONENTY	
ŘÍDÍTKA	Giant Contact XR D-Fuse, 31.8mm, 5-degree backsweep, flare drop XS: 400mm, S: 400mm, M: 420mm, L: 420mm
GRIPY	Liv All Condition
PŘEDSTAVEC	Giant Contact AeroLight, -10-degree XS: 50mm, S: 60mm, M: 70mm, L: 80mm
SEDOVKVA	Giant D-Fuse SL, composite, -5/+15mm offset
SEDLO	Liv Approach
PEDÁLY	-
OSAŽENÍ	
ŘAZENÍ	Shimano GRX RX-820, 2x12
PŘESMYKAČ	Shimano GRX RX-820
PŘEHAZOVAČKA	Shimano GRX RX-820
BRZDY	Shimano GRX RX-820 hydraulic, Shimano RT-70 rotors [F]160mm, [R]160mm
BRZDOVÉ PÁKY	Shimano GRX RX-820 hydraulic
KAZETA	Shimano CS-HG710, 12-speed, 11x36
ŘETĚZ	KMC X12L-1
KLIKY	Shimano GRX RX-820, 31/48 XS: 170mm, S: 170mm, M: 172.5mm, L: 172.5mm
STŘED	Shimano, press fit

KOLA	
RÁFKY	Giant CXR 2 Carbon Disc, [F] 35mm, [R] 35mm
NÁBOJE	[F] Giant alloy, CenterLock, 12mm thru-axle, [R] Giant AR alloy, 3-pawl driver, 36t, CenterLock, 12mm thru-axle
DRÁTY	Sapim Sprint
PLÁŠTĚ	CADEX GX, 700x40c, tubeless
DOPLŇKY	53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position, tubeless prepared, ISC clamp, in-frame storage bag

Cena: akční cena 99 499 Kč (původně 116 999 Kč)

GEOMETRIE

RÁM	XS	S	M	L
	SHORT LONG	SHORT LONG	SHORT LONG	SHORT LONG
Délka sedlové trubky (mm)	390	420	465	500
Úhel sedlové trubky	74,5° 74,4°	74,5° 74,4°	74,5° 74,4°	74,5° 74,4°
Délka horní trubky (mm)	525 525	535 535	545 545	555 555
Délka hlavové trubky (mm)	90	110	140	160
Úhel hlavové trubky	70,0° 69,9°	70,5° 70,4°	71,0° 70,9°	71,0° 70,9°
Offset vidlice (mm)	50	50	50	50
Trail (mm)	78,4 82	75 78,5	71,6 75,1	71,6 75
Rozvor (mm)	1012 1022	1019 1029	1026 1036	1043 1052
Délka řetězové vzpěry (mm)	425 435	425 435	425 435	430 440
Bottom Bracket Drop (mm)	80 81	80 81	80 81	80 81
Stack (mm)	523 524	544 545	574 575	593 594
Reach (mm)	380 379	384 383	386 385	391 389
Výška rámu od země (mm)	681 688	708 715	748 755	779 786
Šířka řídítek (mm)	400	400	420	420
Délka představce (mm)	50	60	70	80
Délka klik (mm)	170	170	172,5	172,5
Rozměr kol	700	700	700	700

Děláme vše pro to, aby veškeré údaje na tomto webu byly správné a aktuální. Přesto si ale musíme vyhradit právo na případné změny specifikací, barevného provedení a cen, a to bez předchozího upozornění. Děkujeme za pochopení.