

DEVOTE ADVANCED 0



SPECIFIKATIONER

RAMME	
STØRRELSER	XS, S, M, L
FARVER	Camel Silk/Chrome
RAMME	Advanced-grade composite, 12x142mm thru-axle, flat mount disc, flip chip - dropout, integrated down tube storage
FORGAFFEL	Advanced-grade composite, full-composite OverDrive steerer, 12mm thru-axle, flat mount disc, FSA stainless upper/lower bearings
KOMPONENTER	
STYR	Giant Contact XR D-Fuse, 31.8mm, 5-degree back sweep, flare drop, XS: 400mm, S: 400mm, M: 420mm, L: 420mm
GREB / STYRBÅND	Liv All Condition
FREMPIND	Giant Contact AeroLight, -10-degree, XS: 50mm, S: 60mm, M: 70mm, L: 80mm
SADELPIND	Giant D-Fuse, composite, -5/+15mm offset
SADEL	Liv Grit
GEARGRUPPE	
SKIFTEGREB	Shimano GRX RX-820, 2x12
FORSKIFTER	Shimano GRX RX-820
BAGSKIFTER	Shimano GRX RX-820
BREMSE	Shimano GRX RX-820 hydraulic, Shimano RT-70 rotors, [F]160mm, [R]160mm
BREMSEGREB	Shimano GRX RX-820 hydraulic
KASSETTE	Shimano CS-HG710, 12-speed, 11x36
KÆDE	KMC X12L-1
KRANKSÆT	Shimano GRX RX-820, 31/48, XS: 170mm, S: 170mm, M: 172.5mm, L: 172.5mm
KRANKBOKS	Shimano, press fit

HJUL	
FÆLGE	Giant CXR 2, [F] 35mm, [R] 35mm
NAV	[F] Giant alloy, CenterLock, 12mm thru-axle, [R] Giant AR alloy, 3-pawl driver, 36t, CenterLock, 12mm thru-axle
EGER	Sapim Sprint
DÆK	Crosscut Grip 45c
EKSTRA	53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position, tubeless prepared, ISC clamp, in-frame storage bag
GRÆNSER	
MAX DÆKSTØRRELSE	53mm

Pris: 34.399,00 kr.

GEOMETRI

RAMME	XS	S	M	L
Sadelrørlængde (mm)	SHORT LONG	SHORT LONG	SHORT LONG	SHORT LONG
Sadelrørvinkel	74,5° 74,4°	74,5° 74,4°	74,5° 74,4°	74,5° 74,4°
Overrørlængde (mm)	525 525	535 535	545 545	555 555
Kronrørlængde (mm)	90	110	140	160
Kronrørvinkel	70,0° 69,9°	70,5° 70,4°	71,0° 70,9°	71,0° 70,9°
Forgaffel fremspring (rake) (mm)	50	50	50	50
Sti (mm)	78,4 82	75 78,5	71,6 75,1	71,6 75
Akselafstand (mm)	1012 1022	1019 1029	1026 1036	1043 1052
Kædestagslængde (mm)	425 435	425 435	425 435	430 440
Krankboks drop (mm)	80 81	80 81	80 81	80 81
Stack (mm)	523 524	544 545	574 575	593 594
Reach (mm)	380 379	384 383	386 385	391 389
Skridthøjde (mm)	681 688	708 715	748 755	779 786
Styrbredde (mm)	400	400	420	420
Frempindslængde (mm)	50	60	70	80
Pedalarmslængde (mm)	165	170	172,5	172,5

Alle de anførte specifikationer kan ændres uden varsel.