

# DEVOTE ADVANCED 0



## SPECS

ΣΚΕΛΕΤΟΣ	
ΜΕΓΕΘΗ	XS, S, M, L
ΧΡΩΜΑΤΑ	Camel Silk/Chrome
ΣΚΕΛΕΤΟΣ	Advanced-grade composite, 12x142mm thru-axle, flat mount disc, flip chip - dropout, integrated down tube storage
ΠΙΡΟΥΝΙ	Advanced-grade composite, full-composite OverDrive steerer, 12mm thru-axle, flat mount disc, FSA stainless upper/lower bearings
ΕΞΑΡΤΗΜΑΤΑ	
ΤΙΜΟΝΙ	Giant Contact XR D-Fuse, 31.8mm, 5-degree back sweep, flare drop, XS: 400mm, S: 400mm, M: 420mm, L: 420mm
GRIPS	Liv All Condition
ΛΑΙΜΟΣ ΤΙΜΟΝΙΟΥ	Giant Contact AeroLight, -10-degree, XS: 50mm, S: 60mm, M: 70mm, L: 80mm
ΛΑΙΜΟΣ ΣΕΛΛΑΣ	Giant D-Fuse, composite, -5/+15mm offset
ΣΕΛΛΑ	Liv Grit
ΜΕΤΑΔΟΣΗ	
ΛΕΒΙΕ ΤΑΧΥΤΗΤΩΝ	Shimano GRX RX-820, 2x12
ΝΤΕΡΑΓΙΕΡ ΕΜΠΡΟΣΘΙΟ	Shimano GRX RX-820
ΝΤΕΡΑΓΙΕΡ ΟΠΙΣΘΙΟ.	Shimano GRX RX-820
ΦΡΕΝΑ	Shimano GRX RX-820 hydraulic, Shimano RT-70 rotors, [F]160mm, [R]160mm
ΜΑΝ'ΕΤΤΕΣ ΦΡΕΝΩΝ	Shimano GRX RX-820 hydraulic
CASETTE Ή ΕΛΕΥΘΕΡΟ	Shimano CS-HG710, 12-speed, 11x36
ΑΛΥΣΙΔΑ	KMC X12L-1
ΔΙΣΚΟΒΡΑΧΙΩΝΑΣ	Shimano GRX RX-820, 31/48, XS: 170mm, S: 170mm, M: 172.5mm, L: 172.5mm
BOTTOM BRACKET	Shimano, press fit

WHEELS	
ΣΤΕΦΑΝΙΑ	Giant CXR 2, [F] 35mm, [R] 35mm
ΚΕΝΤΡΑ	[F] Giant alloy, CenterLock, 12mm thru-axle, [R] Giant AR alloy, 3-pawl driver, 36t, CenterLock, 12mm thru-axle
ΑΚΤΙΝΕΣ	Sapim Sprint
ΕΛΑΣΤΙΚΑ	Crosscut Grip 45c
EXTRAS	53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position, tubeless prepared, ISC clamp, in-frame storage bag
LIMITS	
MAX TIRE CLEARANCE	53mm

## ΓΕΩΜΕΤΡΙΑ

ΣΚΕΛΕΤΟΣ	XS		S		M		L	
	SHORT	LONG	SHORT	LONG	SHORT	LONG	SHORT	LONG
Seat Tube Length (mm)	390	420	420	465	500			
Seat Tube Angle	74,5°   74,4°	74,5°   74,4°	74,5°   74,4°	74,5°   74,4°	74,5°   74,4°			
Top Tube Length (mm)	525   525	535   535	545   545	555   555				
Head Tube Length (mm)	90	110	140	160				
Head Tube Angle	70,0°   69,9°	70,5°   70,4°	71,0°   70,9°	71,0°   70,9°				
Fork Rake (mm)	50	50	50	50				
Trail (mm)	78,4   82	75   78,5	71,6   75,1	71,6   75				
Wheelbase (mm)	1012   1022	1019   1029	1026   1036	1043   1052				
Chain Stay Length (mm)	425   435	425   435	425   435	430   440				
Bottom Bracket Drop (mm)	80   81	80   81	80   81	80   81				
Stack (mm)	523   524	544   545	574   575	593   594				
Reach (mm)	380   379	384   383	386   385	391   389				
Stand Over Height (mm)	681   688	708   715	748   755	779   786				
Handlebar Width (mm)	400	400	420	420				
Stem Length (mm)	50	60	70	80				
Crank Length (mm)	165	170	172,5	172,5				

Όλες οι προδιαγραφές είναι δυνατό να αλλάξουν χωρίς πρότερη ειδοποίηση