

# DEVOTE ADVANCED 0



## SPECS

FRAME	
<b>SIZES</b>	XS, S, M, L
<b>COLOURS</b>	Tiger Red
<b>FRAME</b>	Advanced-grade composite, 12x142mm thru-axle, flat mount disc, flip chip - dropout, integrated down tube storage, integrated cable routing
<b>FORK</b>	Advanced-grade composite, full-composite OverDrive steerer, stainless steel bearings, 12mm thru-axle, flat mount disc
<b>SHOCK</b>	N/A
COMPONENTS	
<b>HANDLEBAR</b>	Giant Contact XR D-Fuse, 31.8mm, 5-degree back sweep, flare drop, alloy XS: 400mm, S: 400mm, M: 420mm, L: 420mm
<b>GRIPS</b>	Liv All Condition
<b>STEM</b>	Giant Contact AeroLight, -10 degree, alloy XS: 50mm, S: 60mm, M: 70mm, L: 80mm
<b>SEATPOST</b>	Giant Contact SL D-Fuse, composite, -5/+15mm offset
<b>SADDLE</b>	Liv Approach
<b>PEDALS</b>	PEDALS NOT SUPPLIED
DRIVETRAIN	
<b>SHIFTERS</b>	Shimano GRX RX-820, 2x12
<b>FRONT DERAILLEUR</b>	Shimano GRX RX-820
<b>REAR DERAILLEUR</b>	Shimano GRX RX-820
<b>BRAKES</b>	Shimano GRX RX-820 hydraulic, Shimano RT-70 rotors [F]160mm, [R]160mm
<b>BRAKE LEVERS</b>	Shimano GRX RX-820 hydraulic
<b>CASSETTE</b>	Shimano CS-HG710, 12-speed, 11x36
<b>CHAIN</b>	KMC X12L-1
<b>CRANKSET</b>	Shimano GRX FC-RX820, 31/48 XS: 165mm, S: 170mm, M: 172.5mm, L: 172.5mm
<b>BOTTOM BRACKET</b>	Shimano, press fit

WHEELS	
<b>RIMS</b>	Giant CXR 2 Carbon Disc WheelSystem, [F] 35mm, [R] 35mm
<b>HUBS</b>	[F] Giant alloy, CenterLock, 12mm thru-axle [R] Giant AR alloy, 3-pawl driver, CenterLock, 12mm thru-axle
<b>SPOKES</b>	Sapim Sprint
<b>TYRES</b>	CADEX AR, 700x40c, tubeless
<b>EXTRAS</b>	factory tubeless set up, ISC clamp, integrated down tube storage bag
LIMITS	
<b>MAX TYRE CLEARANCE</b>	53mm max tyre size in long flip chip position, 45mm max tyre size in short flip chip position
<b>MAX CHAINRING SIZE</b>	SRAM Wide 2x 43-30, 1x 44T. Shimano GRX 2x 48-31, 1x 42T

**Price: £3,799.00**

## GEOMETRY

FRAME	XS		S		M		L	
	SHORT	LONG	SHORT	LONG	SHORT	LONG	SHORT	LONG
Seat Tube Length (mm)	390	420	465	500				
Seat Tube Angle	74.5°   74.4°	74.5°   74.4°	74.5°   74.4°	74.5°   74.4°				
Top Tube Length (mm)	525   525	535   535	545   545	555   555				
Head Tube Length (mm)	90	110	140	160				
Head Tube Angle	70.0°   69.9°	70.5°   70.4°	71.0°   70.9°	71.0°   70.9°				
Fork Rake (mm)	50	50	50	50				
Trail (mm)	78.4   82	75   78.5	71.6   75.1	71.6   75				
Wheelbase (mm)	1012   1022	1019   1029	1026   1036	1043   1052				
Chain Stay Length (mm)	425   435	425   435	425   435	430   440				
Bottom Bracket Drop (mm)	80   81	80   81	80   81	80   81				
Stack (mm)	523   524	544   545	574   575	593   594				
Reach (mm)	380   379	384   383	386   385	391   389				
Stand Over Height (mm)	681   688	708   715	748   755	779   786				
Handlebar Width (mm)	400	400	420	420				
Stem Length (mm)	50	60	70	80				
Crank Length (mm)	165	170	172.5	172.5				
Wheel Size	700	700	700	700				

Every effort has been made to ensure accuracy throughout this website. However, Giant reserves the right to change bike specifications, features, prices and colours without prior notice.