

DEVOTE ADVANCED 0



SPECS

FRAME	
SIZES	XS, S, M, L
COLOURS	Camel Silk/Chrome
FRAME	Advanced-grade composite, 12x142mm thru-axle, flat mount disc, flip chip - dropout, integrated down tube storage
FORK	Advanced-grade composite, full-composite OverDrive steerer, 12mm thru-axle, flat mount disc, FSA stainless upper/lower bearings
COMPONENTS	
HANDLEBAR	Giant Contact XR D-Fuse, 31.8mm, 5-degree back sweep, flare drop, XS: 400mm, S: 400mm, M: 420mm, L: 420mm
GRIPS	Liv All Condition
STEM	Giant Contact AeroLight, -10-degree, XS: 50mm, S: 60mm, M: 70mm, L: 80mm
SEATPOST	Giant D-Fuse, composite, -5/+15mm offset
SADDLE	Liv Grit
DRIVETRAIN	
SHIFTERS	Shimano GRX RX-820, 2x12
FRONT DERAILLEUR	Shimano GRX RX-820
REAR DERAILLEUR	Shimano GRX RX-820
BRAKES	Shimano GRX RX-820 hydraulic, Shimano RT-70 rotors, [F]160mm, [R]160mm
BRAKE LEVERS	Shimano GRX RX-820 hydraulic
CASSETTE	Shimano CS-HG710, 12-speed, 11x36
CHAIN	KMC X12L-1
CRANKSET	Shimano GRX RX-820, 31/48, XS: 165mm, S: 170mm, M: 172.5mm, L: 172.5mm
BOTTOM BRACKET	Shimano, press fit

WHEELS	
RIMS	Giant CXR 2, [F] 35mm, [R] 35mm
HUBS	[F] Giant alloy, CenterLock, 12mm thru-axle, [R] Giant AR alloy, 3-pawl driver, 36t, CenterLock, 12mm thru-axle
SPOKES	Sapim Sprint
TYRES	Crosscut Grip 45c
EXTRAS	53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position, tubeless prepared, ISC clamp, in-frame storage bag
LIMITS	
MAX TIRE CLEARANCE	53mm

Price: €3,949.00

GEOMETRY

FRAME	XS		S		M		L	
	SHORT	LONG	SHORT	LONG	SHORT	LONG	SHORT	LONG
Seat Tube Length (mm)	390	420	465	500				
Seat Tube Angle	74.5° 74.4°	74.5° 74.4°	74.5° 74.4°	74.5° 74.4°				
Top Tube Length (mm)	525 525	535 535	545 545	555 555				
Head Tube Length (mm)	90	110	140	160				
Head Tube Angle	70.0° 69.9°	70.5° 70.4°	71.0° 70.9°	71.0° 70.9°				
Fork Rake (mm)	50	50	50	50				
Trail (mm)	78.4 82	75 78.5	71.6 75.1	71.6 75				
Wheelbase (mm)	1012 1022	1019 1029	1026 1036	1043 1052				
Chain Stay Length (mm)	425 435	425 435	425 435	430 440				
Bottom Bracket Drop (mm)	80 81	80 81	80 81	80 81				
Stack (mm)	523 524	544 545	574 575	593 594				
Reach (mm)	380 379	384 383	386 385	391 389				
Stand Over Height (mm)	681 688	708 715	748 755	779 786				
Handlebar Width (mm)	400	400	420	420				
Stem Length (mm)	50	60	70	80				
Crank Length (mm)	165	170	172.5	172.5				

All specifications listed are subject to change without notice.