

# DEVOTE ADVANCED 0



## TEKNISET TIEDOT

RUNKO	
KOOT	XS, S, M, L
VÄRIT	Camel Silk/Chrome
RUNKO	Advanced-grade composite, 12x142mm thru-axle, flat mount disc, flip chip - dropout, integrated down tube storage
HAARUKKA	Advanced-grade composite, full-composite OverDrive steerer, 12mm thru-axle, flat mount disc, FSA stainless upper/lower bearings
KOMPONENTIT	
OHJAUSTANKO	Giant Contact XR D-Fuse, 31.8mm, 5-degree back sweep, flare drop, XS: 400mm, S: 400mm, M: 420mm, L: 420mm
GRIPIT	Liv All Condition
OHJAINKANNATIN	Giant Contact AeroLight, -10-degree, XS: 50mm, S: 60mm, M: 70mm, L: 80mm
SATULATOLPPA	Giant D-Fuse, composite, -5/+15mm offset
SATULA	Liv Grit
VOIMANSIIRTO	
VAIHDEVIPU	Shimano GRX RX-820, 2x12
ETUVAIHTAJA	Shimano GRX RX-820
TAKAVAIHTAJA	Shimano GRX RX-820
JARRUT	Shimano GRX RX-820 hydraulic, Shimano RT-70 rotors, [F]160mm, [R]160mm
JARRUKAHVAT	Shimano GRX RX-820 hydraulic
RATASPAKKA	Shimano CS-HG710, 12-speed, 11x36
KETJUT	KMC X12L-1
KAMPISARJA	Shimano GRX RX-820, 31/48, XS: 165mm, S: 170mm, M: 172.5mm, L: 172.5mm
KESKIÖ	Shimano, press fit

RENKAAT	
VANTEET	Giant CXR 2, [F] 35mm, [R] 35mm
NAVAT	[F] Giant alloy, CenterLock, 12mm thru-axle, [R] Giant AR alloy, 3-pawl driver, 36t, CenterLock, 12mm thru-axle
PINNAT	Sapim Sprint
RENKAAT	Crosscut Grip 45c
LISÄTIEDOT	53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position, tubeless prepared, ISC clamp, in-frame storage bag
RAJOITTEET	
MAX RENGASVARA	53mm

Suositus hinta: 4 599,00 €

## GEOMETRIA

RUNKO	XS	S	M	L
	SHORT   LONG	SHORT   LONG	SHORT   LONG	SHORT   LONG
Satulaputken pituus (mm)	390	420	465	500
Satulaputken kulma	74,5°   74,4°	74,5°   74,4°	74,5°   74,4°	74,5°   74,4°
Vaakaputken pituus (mm)	525   525	535   535	545   545	555   555
Emäputken pituus (mm)	90	110	140	160
Emäputken kulma	70,0°   69,9°	70,5°   70,4°	71,0°   70,9°	71,0°   70,9°
Haarukan offset (mm)	50	50	50	50
Trail-mitta (mm)	78,4   82	75   78,5	71,6   75,1	71,6   75
Akseliväli (mm)	1012   1022	1019   1029	1026   1036	1043   1052
Takahaarukan alaputken pituus (mm)	425   435	425   435	425   435	430   440
Keskion pudotus (mm)	80   81	80   81	80   81	80   81
Stack-mitta (mm)	523   524	544   545	574   575	593   594
Reach-mitta (mm)	380   379	384   383	386   385	391   389
Standover-mitta (mm)	681   688	708   715	748   755	779   786
Ohjaustangon leveys (mm)	400	400	420	420
Ohjainkannattimen pituus (mm)	50	60	70	80
Kammen pituus (mm)	165	170	172,5	172,5

Kaikki ilmoitetut tekniset tiedot voivat muuttua ilman erillistä ilmoitusta.