

# DEVOTE ADVANCED 0



## SPEZIFIKATIONEN

RAHMEN	
GRÖSSEN	XS, S, M, L
FARBE	Camel Silk/Chrome
RAHMEN	Advanced-grade composite, 12x142mm thru-axle, flat mount disc, flip chip - dropout, integrated down tube storage
GABEL	Advanced-grade composite, full-composite OverDrive steerer, 12mm thru-axle, flat mount disc, FSA stainless upper/lower bearings
KOMPONENTEN	
LENKER	Giant Contact XR D-Fuse, 31.8mm, 5-degree back sweep, flare drop, XS: 400mm, S: 400mm, M: 420mm, L: 420mm
GRIFFE	Liv All Condition
VORBAU	Giant Contact AeroLight, -10-degree, XS: 50mm, S: 60mm, M: 70mm, L: 80mm
SATTELSTÜTZE	Giant D-Fuse, composite, -5/+15mm offset
SATTEL	Liv Grit
ANTRIEB	
SCHALTHEBEL	Shimano GRX RX-820, 2x12
UMWERFER	Shimano GRX RX-820
SCHALTWERK	Shimano GRX RX-820
BREMSEN	Shimano GRX RX-820 hydraulic, Shimano RT-70 rotors, [F]160mm, [R]160mm
BREMSHEBEL	Shimano GRX RX-820 hydraulic
KASSETTE	Shimano CS-HG710, 12-speed, 11x36
KETTE	KMC X12L-1
KURBEL	Shimano GRX RX-820, 31/48, XS: 165mm, S: 170mm, M: 172.5mm, L: 172.5mm
TRETLAGER	Shimano, press fit

LAUFRÄDER	
FELGEN	Giant CXR 2, [F] 35mm, [R] 35mm
NABE	[F] Giant alloy, CenterLock, 12mm thru-axle, [R] Giant AR alloy, 3-pawl driver, 36t, CenterLock, 12mm thru-axle
SPEICHEN	Sapim Sprint
REIFEN	Crosscut Grip 45c
EXTRAS	53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position, tubeless prepared, ISC clamp, in-frame storage bag
LIMITS	
MAX TIRE CLEARANCE	53mm

## GEOMETRIEDATEN

RAHMEN	XS		S		M		L	
	SHORT	LONG	SHORT	LONG	SHORT	LONG	SHORT	LONG
Sitzrohlänge (mm)	390	420	465	500				
Sitzrohrwinkel	74.5°   74.4°	74.5°   74.4°	74.5°   74.4°	74.5°   74.4°	74.5°   74.4°			
Oberrohrlänge (mm)	525   525	535   535	545   545	555   555				
Steuerrohr-Länge (mm)	90	110	140	160				
Steuerrohr-Winkel	70.0°   69.9°	70.5°   70.4°	71.0°   70.9°	71.0°   70.9°				
Gabelneigung (mm)	50	50	50	50				
Trail (mm)	78.4   82	75   78.5	71.6   75.1	71.6   75				
Radstand (mm)	1012   1022	1019   1029	1026   1036	1043   1052				
Kettenstreben-Länge (mm)	425   435	425   435	425   435	430   440				
Tretlager-Höhe (mm)	80   81	80   81	80   81	80   81				
Stack (mm)	523   524	544   545	574   575	593   594				
Reach (mm)	380   379	384   383	386   385	391   389				
Überstandshöhe (mm)	681   688	708   715	748   755	779   786				
Lenkerbreite (mm)	400	400	420	420				
Vorbaulänge (mm)	50	60	70	80				
Kurbellänge (mm)	165	170	172.5	172.5				

Spezifikations-, Preis- und Farbänderungen vorbehalten.