

DEVOTE ADVANCED 0



SPECIFIKACIJE

OKVIR	
VELIČINE	XS, S, M, L
BOJE	Camel Silk/Chrome
OKVIR	Advanced-grade composite, 12x142mm thru-axle, flat mount disc, flip chip - dropout, integrated down tube storage
VILICA	Advanced-grade composite, full-composite OverDrive steerer, 12mm thru-axle, flat mount disc, FSA stainless upper/lower bearings
KOMPONENTE	
VOLAN	Giant Contact XR D-Fuse, 31.8mm, 5-degree back sweep, flare drop, XS: 400mm, S: 400mm, M: 420mm, L: 420mm
GRIPS	Liv All Condition
LULA VOLANA	Giant Contact AeroLight, -10-degree, XS: 50mm, S: 60mm, M: 70mm, L: 80mm
CIJEV SJEDALA	Giant D-Fuse, composite, -5/+15mm offset
SJEDALO	Liv Grit
POGON	
RUČICE MJENJAČA	Shimano GRX RX-820, 2x12
PREDNJI MJENJAČ	Shimano GRX RX-820
STRAŽNJI MJENJAČ	Shimano GRX RX-820
KOČNICE	Shimano GRX RX-820 hydraulic, Shimano RT-70 rotors, [F]160mm, [R]160mm
RUČICE KOČNICA	Shimano GRX RX-820 hydraulic
KAZETA	Shimano CS-HG710, 12-speed, 11x36
LANAC	KMC X12L-1
POGON	Shimano GRX RX-820, 31/48, XS: 165mm, S: 170mm, M: 172.5mm, L: 172.5mm
OSOVINA POGONA (BB)	Shimano, press fit

KOTAČI	
OBRUČI	Giant CXR 2, [F] 35mm, [R] 35mm
NABE	[F] Giant alloy, CenterLock, 12mm thru-axle, [R] Giant AR alloy, 3-pawl driver, 36t, CenterLock, 12mm thru-axle
ŽBICE	Sapim Sprint
GUME	Crosscut Grip 45c
DODACI	53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position, tubeless prepared, ISC clamp, in-frame storage bag
LIMITS	
MAX TIRE CLEARANCE	53mm

GEOMETRIJA

OKVIR	XS	S	M
	SHORT	LONG SHORT	LONG SHORT
Dužina cijevi sjedala (mm)	390	420	465
Kut cijevi sjedala	74,5° 74,4°	74,5° 74,4°	74,5° 74
Dužina gornje cijevi (mm)	525 525	535 535	545 545
Dužina prednje cijevi (mm)	90	110	140
Kut vilice	70,0° 69,9°	70,5° 70,4°	71,0° 70
Zakrivljenost vilice (offset) (mm)	50	50	50
Staza (mm)	78,4 82	75 78,5	71,6 75,
Međuosovinski razmak kotača (mm)	1012 1022	1019 1029	1026 10
Dužina od osovine pogona do osovine zadnjeg kotača (CS) (mm)	425 435	425 435	425 435
Položaj osovine pogona (mm)	80 81	80 81	80 81
Vertikalna dužina od osovine pogona do glave okvira (stack) (mm)	523 524	544 545	574 575
Horizontalna dužina od osovine pogona do glave okvira (reach) (mm)	380 379	384 383	386 385
Prekoračna visina (mm)	681 688	708 715	748 755
Širina volana (mm)	400	400	420
Dužina lule volana (mm)	50	60	70
Dužina poluge pedale (mm)	165	170	172,5

Sve navedene specifikacije podložne su promjeni bez prethodne najave.