

DEVOTE ADVANCED 0



SPECIFICATIES

FRAME	
MATEN	XS, S, M, L
KLEUREN	Camel Silk/Chrome
FRAME	Advanced-grade composite, 12x142mm thru-axle, flat mount disc, flip chip – dropout, integrated down tube storage
VOORVORK	Advanced-grade composite, full-composite OverDrive steerer, 12mm thru-axle, flat mount disc, FSA stainless upper/lower bearings
ONDERDELEN	
STUUR	Giant Contact XR D-Fuse, 31.8mm, 5-degree back sweep, flare drop, XS: 400mm, S: 400mm, M: 420mm, L: 420mm
HANDVATTEN	Liv All Condition
STUURPEN	Giant Contact AeroLight, -10-degree, XS: 50mm, S: 60mm, M: 70mm, L: 80mm
ZADELLEN	Giant D-Fuse, composite, -5/+15mm offset
ZADEL	Liv Grit
AFMONTAGE	
SHIFTERS	Shimano GRX RX-820, 2x12
VOORDERAILLEUR	Shimano GRX RX-820
ACHTTERDERAILLEUR	Shimano GRX RX-820
REMMEN	Shimano GRX RX-820 hydraulic, Shimano RT-70 rotors, [F]160mm, [R]160mm
REMHENDELS	Shimano GRX RX-820 hydraulic
CASSETTE	Shimano CS-HG710, 12-speed, 11x36
AANDRIJVING	KMC X12L-1
CRANKSET	Shimano GRX RX-820, 31/48, XS: 170mm, S: 170mm, M: 172.5mm, L: 172.5mm
BOTTOM BRACKET	Shimano, press fit

WIELSET	
VELGEN	Giant CXR 2, [F] 35mm, [R] 35mm
NAVEN	[F] Giant alloy, CenterLock, 12mm thru-axle, [R] Giant AR alloy, 3-pawl driver, 36t, CenterLock, 12mm thru-axle
SPAKEN	Sapim Sprint
BANDEN	Crosscut Grip 45c
EXTRA'S	53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position, tubeless prepared, ISC clamp, in-frame storage bag
LIMITS	
MAXIMALE BANDENVRIJHEID	53mm

Adviesprijs: € 4.299,00

GEOMETRIE

FRAME	XS	S	M	L
	SHORT LONG	SHORT LONG	SHORT LONG	SHORT LONG
Zitbuis Lengte (mm)	390	420	465	500
Zitbuis Hoek	74,5° 74,4°	74,5° 74,4°	74,5° 74,4°	74,5° 74,4°
Frame Lengte (horizontaal) (mm)	525 525	535 535	545 545	555 555
Balhoofdbuis Lengte (mm)	90	110	140	160
Balhoofdbuis Hoek	70,0° 69,9°	70,5° 70,4°	71,0° 70,9°	71,0° 70,9°
Vork Sprong (mm)	50	50	50	50
Naloop (mm)	78,4 82	75 78,5	71,6 75,1	71,6 75
Wielbasis (mm)	1012 1022	1019 1029	1026 1036	1043 1052
Liggende achtersvork lengte (mm)	425 435	425 435	425 435	430 440
Bottom Bracket Drop (mm)	80 81	80 81	80 81	80 81
Stack (mm)	523 524	544 545	574 575	593 594
Reach (mm)	380 379	384 383	386 385	391 389
Stand Over Height (mm)	681 688	708 715	748 755	779 786
Stuur breedte (mm)	400	400	420	420
Stuurpen Lengte (mm)	50	60	70	80
Cranklengte (mm)	165	170	172,5	172,5

Deze specificaties zijn met de grootste zorgvuldigheid samengesteld. Specificaties, beschikbaarheid, prijzen en kleuren kunnen echter zonder vooraankondiging wijzigen.