

DEVOTE ADVANCED 0



SPECIFICATIES

FRAME	
MATEN	XS, S, M, L
KLEUREN	Tiger Red
FRAME	Advanced-grade composite, 12x142mm thru-axle, flat mount disc, flip chip - dropout, integrated down tube storage, integrated cable routing
VOORVORK	Advanced-grade composite, full-composite OverDrive steerer, stainless steel bearings, 12mm thru-axle, flat mount disc
DEMPER	N/A
ONDERDELEN	
STUUR	Giant Contact XR D-Fuse, 31.8mm, 5-degree back sweep, flare drop, alloy XS: 400mm, S: 400mm, M: 420mm, L: 420mm
HANDVATTEN	Liv All Condition
STUURPEN	Giant Contact AeroLight, -10 degree, alloy XS: 50mm, S: 60mm, M: 70mm, L: 80mm
ZADELPEN	Giant Contact SL D-Fuse, composite, -5/+15mm offset
ZADEL	Liv Approach
PEDALEN	N/A
AFMONTAGE	
SHIFTERS	Shimano GRX RX-820, 2x12
VOORDERAILLEUR	Shimano GRX RX-820
ACHTERDERAILLEUR	Shimano GRX RX-820
REMMEN	Shimano GRX RX-820 hydraulic, Shimano RT-70 rotors [F]160mm, [R]160mm
REMHENDELS	Shimano GRX RX-820 hydraulic
CASSETTE	Shimano CS-HG710, 12-speed, 11x36
AANDRIJVING	KMC X12L-1
CRANKSET	Shimano GRX FC-RX820, 31/48 XS: 165mm, S: 170mm, M: 172.5mm, L: 172.5mm
BOTTOM BRACKET	Shimano, press fit

WIELSET	
VELGEN	Giant CXR 2 Carbon Disc WheelSystem, [F] 35mm, [R] 35mm
NAVEN	[F] Giant alloy, CenterLock, 12mm thru-axle [R] Giant AR alloy, 3-pawl driver, CenterLock, 12mm thru-axle
SPAKEN	Sapim Sprint
BANDEN	CADEX AR, 700x40c, tubeless
EXTRA'S	53mm max tire size in long flip chip position, 45mm max tire size in short flip chip position, tubeless prepared, ISC clamp, integrated down tube storage bag

Adviesprijs: € 4.399,00

GEOMETRIE

FRAME	XS		S		M		L	
	SHORT	LONG	SHORT	LONG	SHORT	LONG	SHORT	LONG
Zitbuis lengte (mm)	390	420	465	500				
Zitbuis hoek	74,5° 74,4°	74,5° 74,4°	74,5° 74,4°	74,5° 74,4°				
Frame Lengte (horizontaal) (mm)	525 525	535 535	545 545	555 555				
Balhoofdruis Lengte (mm)	90	110	140	160				
Balhoofdruis Hoek	70,0° 69,9°	70,5° 70,4°	71,0° 70,9°	71,0° 70,9°				
Vork Sprong (mm)	50	50	50	50				
Naloop (mm)	78,4 82	75 78,5	71,6 75,1	71,6 75				
Wielbasis (mm)	1012 1022	1019 1029	1026 1036	1043 1052				
Liggende achtervork lengte (mm)	425 435	425 435	425 435	430 440				
Bottom Bracket Drop (mm)	80 81	80 81	80 81	80 81				
Stack (mm)	523 524	544 545	574 575	593 594				
Reach (mm)	380 379	384 383	386 385	391 389				
Stand Over Height (mm)	681 688	708 715	748 755	779 786				
Stuur breedte (mm)	400	400	420	420				
Stuurpen Lengte (mm)	50	60	70	80				
Cranklengte (mm)	165	170	172,5	172,5				
Wielmaat	700	700	700	700				

Deze specificaties zijn met de grootste zorgvuldigheid samengesteld. Specificaties, beschikbaarheid, prijzen en kleuren kunnen echter zonder voor aankondiging wijzigen.