

DEVOTE ADVANCED 0



SPECS

RAMME	
STØRRELSE	XS, S, M, L
FARGE	Tiger Red
RAMME	Advanced-grade composite, 12x142mm thru-axle, flat mount disc, flip chip - dropout, integrated down tube storage
GAFFEL	Advanced-grade composite, full-composite OverDrive steerer, 12mm thru-axle, flat mount disc, FSA stainless upper/lower bearings
DEMPER	N/A
KOMPONENTER	
STYRE	Giant Contact XR D-Fuse, 31.8mm, 5-degree backsweep, flare drop XS: 400mm, S: 400mm, M: 420mm, L: 420mm
GRIPS	Liv All Condition
STYRSTEM	Giant Contact AeroLight, -10-degree XS: 50mm, S: 60mm, M: 70mm, L: 80mm
SETEPINNE	Giant D-Fuse SL, composite, -5/+15mm offset
SADEL	Liv Approach
PEDALER	N/A
DRIVVERK	
GIRHENDLER	Shimano GRX RX-820, 2x12
FRONTGIR	Shimano GRX RX-820
BAKGIR	Shimano GRX RX-820
BREMSEER	Shimano GRX RX-820 hydraulic, Shimano RT-70 rotors [F]160mm, [R]160mm
BREMSEHENDLER	Shimano GRX RX-820 hydraulic
KASSETT	Shimano CS-HG710, 12-speed, 11x36
KJEDE	KMC X12L-1
KRANK	Shimano GRX RX-820, 31/48 XS: 170mm, S: 170mm, M: 172.5mm, L: 172.5mm
BOTTOM BRACKET	Shimano, press fit

HJUL	
FELG	Giant CXR 2 Carbon Disc, [F] 35mm, [R] 35mm
NAV	[F] Giant alloy, CenterLock, 12mm thru-axle, [R] Giant AR alloy, 3-pawl driver, 36t, CenterLock, 12mm thru-axle
EIKE	Sapim Sprint
DEKK	CADEX GX, 700x40c, tubeless
EXTRAS	53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position, tubeless prepared, ISC clamp, in-frame storage bag

GEOMETRI

RAMME	XS	S	M	L
	SHORT LONG	SHORT LONG	SHORT LONG	SHORT LONG
Seat Tube Length (mm)	390	420	465	500
Seat Tube Angle	74,5° 74,4°	74,5° 74,4°	74,5° 74,4°	74,5° 74,4°
Top Tube Length (mm)	525 525	535 535	545 545	555 555
Head Tube Length (mm)	90	110	140	160
Head Tube Angle	70,0° 69,9°	70,5° 70,4°	71,0° 70,9°	71,0° 70,9°
Fork Rake (mm)	50	50	50	50
Trail (mm)	78,4 82	75 78,5	71,6 75,1	71,6 75
Wheelbase (mm)	1012 1022	1019 1029	1026 1036	1043 1052
Chain Stay Length (mm)	425 435	425 435	425 435	430 440
Bottom Bracket Drop (mm)	80 81	80 81	80 81	80 81
Stack (mm)	523 524	544 545	574 575	593 594
Reach (mm)	380 379	384 383	386 385	391 389
Stand Over Height (mm)	681 688	708 715	748 755	779 786
Handlebar Width (mm)	400	400	420	420
Stem Length (mm)	50	60	70	80
Crank Length (mm)	170	170	172,5	172,5
Wheel Size	700	700	700	700

Alle spesifikasjonene kan endres uten varsel.