

DEVOTE ADVANCED 0



SPECS

| CADRU | |
|-----------------------------------|---|
| MARIMI | XS, S, M, L |
| CULORI | Camel Silk/Chrome |
| CADRU | Advanced-grade composite, 12x142mm thru-axle, flat mount disc, flip chip - dropout, integrated down tube storage |
| FURCA | Advanced-grade composite, full-composite OverDrive steerer, 12mm thru-axle, flat mount disc, FSA stainless upper/lower bearings |
| COMPONENTE | |
| GHIDON | Giant Contact XR D-Fuse, 31.8mm, 5-degree back sweep, flare drop, XS: 400mm, S: 400mm, M: 420mm, L: 420mm |
| GRIPS | Liv All Condition |
| PIPA | Giant Contact AeroLight, -10-degree, XS: 50mm, S: 60mm, M: 70mm, L: 80mm |
| TIJA SA | Giant D-Fuse, composite, -5/+15mm offset |
| SA | Liv Grit |
| SISTEMUL DE SCHIMBARE A VITEZELOR | |
| MANETE SCHIMBATOR | Shimano GRX RX-820, 2x12 |
| SCHIMBATOR FATA | Shimano GRX RX-820 |
| SCHIMBATOR SPATE | Shimano GRX RX-820 |
| FRANE | Shimano GRX RX-820 hydraulic, Shimano RT-70 rotors, [F]160mm, [R]160mm |
| MANETE FRANA | Shimano GRX RX-820 hydraulic |
| PINIOANE | Shimano CS-HG710, 12-speed, 11x36 |
| LANT | KMC X12L-1 |
| ANGRENAJ | Shimano GRX RX-820, 31/48, XS: 170mm, S: 170mm, M: 172.5mm, L: 172.5mm |
| BOTTOM BRACKET | Shimano, press fit |

| ROTI | |
|---------------------------|---|
| JANTE | Giant CXR 2, [F] 35mm, [R] 35mm |
| BUTUCI | [F] Giant alloy, CenterLock, 12mm thru-axle, [R] Giant AR alloy, 3-pawl driver, 36t, CenterLock, 12mm thru-axle |
| SPITE | Sapim Sprint |
| ANVELOPE | Crosscut Grip 45c |
| EXTRAS | 53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position, tubeless prepared, ISC clamp, in-frame storage bag |
| LIMITS | |
| MAX TIRE CLEARANCE | 53mm |

GEOMETRIE

| CADRU | XS | | S | | M | | L | |
|--------------------------|---------------|---------------|---------------|---------------|---------------|---------------|-------|------|
| | SHORT | LONG | SHORT | LONG | SHORT | LONG | SHORT | LONG |
| Seat Tube Length (mm) | 390 | 420 | 420 | 465 | 465 | 500 | | |
| Seat Tube Angle | 74,5° 74,4° | 74,5° 74,4° | 74,5° 74,4° | 74,5° 74,4° | 74,5° 74,4° | 74,5° 74,4° | | |
| Top Tube Length (mm) | 525 525 | 535 535 | 545 545 | 555 555 | | | | |
| Head Tube Length (mm) | 90 | 110 | 140 | 160 | | | | |
| Head Tube Angle | 70,0° 69,9° | 70,5° 70,4° | 71,0° 70,9° | 71,0° 70,9° | | | | |
| Fork Rake (mm) | 50 | 50 | 50 | 50 | | | | |
| Trail (mm) | 78,4 82 | 75 78,5 | 71,6 75,1 | 71,6 75 | | | | |
| Wheelbase (mm) | 1012 1022 | 1019 1029 | 1026 1036 | 1043 1052 | | | | |
| Chain Stay Length (mm) | 425 435 | 425 435 | 425 435 | 430 440 | | | | |
| Bottom Bracket Drop (mm) | 80 81 | 80 81 | 80 81 | 80 81 | | | | |
| Stack (mm) | 523 524 | 544 545 | 574 575 | 593 594 | | | | |
| Reach (mm) | 380 379 | 384 383 | 386 385 | 391 389 | | | | |
| Stand Over Height (mm) | 681 688 | 708 715 | 748 755 | 779 786 | | | | |
| Handlebar Width (mm) | 400 | 400 | 420 | 420 | | | | |
| Stem Length (mm) | 50 | 60 | 70 | 80 | | | | |
| Crank Length (mm) | 165 | 170 | 172,5 | 172,5 | | | | |

Toate specificatiile enumerate se pot schimba fara notificare prealabila.