

DEVOTE ADVANCED 0



ŠPECIFIKÁCIE

RÁM	
VELKOSTI	XS, S, M, L
FARBY	Camel Silk/Chrome
RÁM	Advanced-grade composite, 12x142mm thru-axle, flat mount disc, flip chip - dropout, integrated down tube storage
VIDLICA	Advanced-grade composite, full-composite OverDrive steerer, 12mm thru-axle, flat mount disc, FSA stainless upper/lower bearings
KOMPONENTY	
RIADIDLÁ	Giant Contact XR D-Fuse, 31.8mm, 5-degree back sweep, flare drop, XS: 400mm, S: 400mm, M: 420mm, L: 420mm
GRIPY	Liv All Condition
PREDSTAVEC	Giant Contact AeroLight, -10-degree, XS: 50mm, S: 60mm, M: 70mm, L: 80mm
SEDLOVKA	Giant D-Fuse, composite, -5/+15mm offset
SEDADLO	Liv Grit
POHON	
RAZENIE	Shimano GRX RX-820, 2x12
PREŠMYKAČ	Shimano GRX RX-820
PREHADZOVAČKA	Shimano GRX RX-820
BRZDY	Shimano GRX RX-820 hydraulic, Shimano RT-70 rotors, [F]160mm, [R]160mm
BRZDOVÉ PÁKY	Shimano GRX RX-820 hydraulic
KAZETA	Shimano CS-HG710, 12-speed, 11x36
REŤAZ	KMC X12L-1
KLUKY	Shimano GRX RX-820, 31/48, XS: 170mm, S: 170mm, M: 172.5mm, L: 172.5mm
STREDOVÉ ZLOŽENIE	Shimano, press fit

KOLESÁ	
RÁFIKY	Giant CXR 2, [F] 35mm, [R] 35mm
NÁBOJE	[F] Giant alloy, CenterLock, 12mm thru-axle, [R] Giant AR alloy, 3-pawl driver, 36t, CenterLock, 12mm thru-axle
ŠPICE	Sapim Sprint
PNEUMATIKY	Crosscut Grip 45c
DOPLNKY	53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position, tubeless prepared, ISC clamp, in-frame storage bag
LIMITY	
MAXIMÁLNA ŠÍRKA PNEUMATÍK	53mm

Cena: 4 299 €

GEOMETRIA

RÁM	XS	S	M	L	
Dĺžka sedlovej trubky (mm)	SHORT LONG SHORT LONG SHORT LONG SHORT LON	390	420	465	500
Uhol sedlovej trubky	74,5° 74,4°	74,5° 74,4°	74,5° 74,4°	74,5° 74,4°	74,5° 74,4°
Dĺžka hornej rámovej trubky (mm)	525 525	535 535	545 545	555 555	
Dĺžka hlavovej trubky (mm)	90	110	140	160	
Uhol hlavovej trubky	70,0° 69,9°	70,5° 70,4°	71,0° 70,9°	71,0° 70,9°	
Offset vidlice (mm)	50	50	50	50	
Trail (mm)	78,4 82	75 78,5	71,6 75,1	71,6 75	
Rázvor (mm)	1012 1022	1019 1029	1026 1036	1043 1052	
Dĺžka zadnej stavby (mm)	425 435	425 435	425 435	430 440	
Rozdiel zadnej voči stredovej osi - BB DROP (mm)	80 81	80 81	80 81	80 81	
Stack - výška riadenia (mm)	523 524	544 545	574 575	593 594	
Reach (mm)	380 379	384 383	386 385	391 389	
Výška rámu od zeme (mm)	681 688	708 715	748 755	779 786	
Šírka riaditok (mm)	400	400	420	420	
Dĺžka predstavca (mm)	50	60	70	80	
Dĺžka kľúk (mm)	165	170	172,5	172,5	

Všetky ceny a špecifikácie sa môžu zmeniť bez predchádzajúceho upozornenia.