

# DEVOTE ADVANCED 0



## SPECS

RAM	
STORLEKAR	XS, S, M, L
FÄRGER	Camel Silk/Chrome
RAM	Advanced-grade composite, 12x142mm thru-axle, flat mount disc, flip chip - dropout, integrated down tube storage
GAFFEL	Advanced-grade composite, full-composite OverDrive steerer, 12mm thru-axle, flat mount disc, FSA stainless upper/lower bearings
KOMPONENTER	
STYRE	Giant Contact XR D-Fuse, 31.8mm, 5-degree back sweep, flare drop, XS: 400mm, S: 400mm, M: 420mm, L: 420mm
GREPPAR	Liv All Condition
STAM	Giant Contact AeroLight, -10-degree, XS: 50mm, S: 60mm, M: 70mm, L: 80mm
SADELSTOLPE	Giant D-Fuse, composite, -5/+15mm offset
SADEL	Liv Grit
DRIVLINJA	
VÄXLAR	Shimano GRX RX-820, 2x12
FRAMVÄXEL	Shimano GRX RX-820
BAKVÄXEL	Shimano GRX RX-820
BROMSAR	Shimano GRX RX-820 hydraulic, Shimano RT-70 rotors, [F]160mm, [R]160mm
BROMSSPAKAR	Shimano GRX RX-820 hydraulic
KASSETT	Shimano CS-HG710, 12-speed, 11x36
KEDJA	KMC X12L-1
VEVPARTI	Shimano GRX RX-820, 31/48, XS: 165mm, S: 170mm, M: 172.5mm, L: 172.5mm
BROMSREGLAGE	Shimano, press fit

HJUL	
FÄLGAR	Giant CXR 2, [F] 35mm, [R] 35mm
NAV	[F] Giant alloy, CenterLock, 12mm thru-axle, [R] Giant AR alloy, 3-pawl driver, 36t, CenterLock, 12mm thru-axle
EKRAR	Sapim Sprint
DÄCK	Crosscut Grip 45c
EXTRAFUNKTIONER	53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position, tubeless prepared, ISC clamp, in-frame storage bag
GRÄNSER	
MAX DÄCKAVSTÅND	53mm

Price: 51 990,00 kr

## GEOMETRY

RAM	XS		S		M		L	
	SHORT	LONG	SHORT	LONG	SHORT	LONG	SHORT	LONG
Längd sadelrör (mm)	390		420		465		500	
Vinkel sadelrör	74,5°	74,4°	74,5°	74,4°	74,5°	74,4°	74,5°	74,4°
Topprörets längd (mm)	525	525	535	535	545	545	555	555
Styrhuvud Längd (mm)	90		110		140		160	
Vinkel styrhuvud	70,0°	69,9°	70,5°	70,4°	71,0°	70,9°	71,0°	70,9°
Gaffelvinkel (mm)	50		50		50		50	
Spår (mm)	78,4	82	75	78,5	71,6	75,1	71,6	75
Hjulbas (mm)	1012	1022	1019	1029	1026	1036	1043	1052
Kedjestagslängd (mm)	425	435	425	435	425	435	430	440
Nedre fäste Drop (mm)	80	81	80	81	80	81	80	81
Stack (mm)	523	524	544	545	574	575	593	594
Reach (mm)	380	379	384	383	386	385	391	389
Stå över höjden (mm)	681	688	708	715	748	755	779	786
Styrets bredd (mm)	400		400		420		420	
Stamlängd (mm)	50		60		70		80	
Vevlängd (mm)	165		170		172,5		172,5	

All specifications listed are subject to change without notice.