

# DEVOTE ADVANCED 1



## SPECS

ΣΚΕΛΕΤΟΣ	
ΜΕΓΕΘΗ	XS, S, M, L
ΧΡΩΜΑΤΑ	Lavender Blush
ΣΚΕΛΕΤΟΣ	Advanced-grade composite, 12x142mm thru-axle, flat mount disc, flip chip - dropout, integrated down tube storage
ΠΙΡΟΥΝΙ	Advanced-grade composite, full-composite OverDrive steerer, 12mm thru-axle, flat mount disc, FSA stainless upper/lower bearings
ΕΞΑΡΤΗΜΑΤΑ	
ΤΙΜΟΝΙ	Giant Contact XR D-Fuse, 31.8mm, 5-degree back sweep, flare drop, XS: 400mm, S: 400mm, M: 420mm, L: 420mm
GRIPS	Liv All Condition
ΛΑΙΜΟΣ ΤΙΜΟΝΙΟΥ	Giant Contact AeroLight, -10-degree, XS: 50mm, S: 60mm, M: 70mm, L: 80mm
ΛΑΙΜΟΣ Σ'ΕΛΛΑΣ	Post Moderne, dropper, 30mm suspension, XS: 75mm, S: 75mm, M: 75mm, L: 100mm
Σ'ΕΛΛΑ	Liv Grit
ΜΕΤΑΔΟΣΗ	
ΛΕΒΙΕ ΤΑΧΥΤΗΤΩΝ	SRAM Apex 1, 1x12
ΝΤΕΡΑΓΓΙΕΡ ΕΜΠΡΟΣΘΙΟ	N/A
ΝΤΕΡΑΓΓΙΕΡ ΟΠΙΣΘΙΟ.	SRAM Apex XPLR
ΦΡΕΝΑ	SRAM Apex hydraulic, Giant MPH rotors, [F]160mm, [R]160mm
ΜΑΝΕΤΤΕΣ ΦΡΕΝΩΝ	SRAM Apex hydraulic, left lever dropper switch
CASETTE Ή ΕΛΕΥΘΕΡΟ	SRAM PG-1231 D1 XPLR, 12-speed, 11x44
ΑΛΥΣΙΔΑ	SRAM Apex 12SCN-APX-D1
ΔΙΣΚΟΒΡΑΧΙΩΝΑΣ	SRAM Apex 1 Wide DUB, 40t, XS: 165mm, S: 170mm, M: 172.5mm, L: 172.5mm
BOTTOM BRACKET	SRAM DUB, press fit

WHEELS	
ΣΤΕΦΑΝΙΑ	Giant P-X2 Disc, alloy
ΚΕΝΤΡΑ	Giant alloy, 12mm thru-axle
ΑΚΤΙΝΕΣ	Sapim
ΕΛΑΣΤΙΚΑ	Giant Crosscut Grip, 700x45c, tubeless
EXTRAS	Giant 1x chain guide, tubeless prepared, 53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position, ISC clamp, in-frame storage bag
LIMITS	
MAX TIRE CLEARANCE	53mm

## ΓΕΩΜΕΤΡΙΑ

ΣΚΕΛΕΤΟΣ	XS	S	M	L
	SHORT   LONG	SHORT   LONG	SHORT   LONG	SHORT   LONG
Seat Tube Length (mm)	390	420	465	500
Seat Tube Angle	74,5°   74,4°	74,5°   74,4°	74,5°   74,4°	74,5°   74,4°
Top Tube Length (mm)	525   525	535   535	545   545	555   555
Head Tube Length (mm)	90	110	140	160
Head Tube Angle	70,0°   69,9°	70,5°   70,4°	71,0°   70,9°	71,0°   70,9°
Fork Rake (mm)	50	50	50	50
Trail (mm)	78,4   82	75   78,5	71,6   75,1	71,6   75
Wheelbase (mm)	1012   1022	1019   1029	1026   1036	1043   1052
Chain Stay Length (mm)	425   435	425   435	425   435	430   440
Bottom Bracket Drop (mm)	80   81	80   81	80   81	80   81
Stack (mm)	523   524	544   545	574   575	593   594
Reach (mm)	380   379	384   383	386   385	391   389
Stand Over Height (mm)	681   688	708   715	748   755	779   786
Handlebar Width (mm)	400	400	420	420
Stem Length (mm)	50	60	70	80
Crank Length (mm)	165	170	172,5	172,5

Όλες οι προδιαγραφές είναι δυνατό να αλλάξουν χωρίς πρότερη ειδοποίηση