

DEVOTE ADVANCED 1



SPECS

FRAME	
SIZES	XS, S, M, L
COLOURS	Ice Age
FRAME	Advanced-grade composite, 12x142mm thru-axle, flat mount disc, flip chip – dropout, integrated down tube storage
FORK	Advanced-Grade Composite, full-composite OverDrive steerer, 12mm thru-axle, disc
SHOCK	N/A
COMPONENTS	
HANDLEBAR	Giant Contact XR D-Fuse, 31.8mm XS:40cm, S:40cm, M:42cm, L:42cm
GRIPS	Liv All Condition
STEM	Giant Contact AeroLight, -10-degree XS: 50mm, S: 60mm, M: 70mm, L: 80mm
SEATPOST	Postmodern, dropper, 30.9mm with 25mm of suspension XS:365mm / 75mm drop S:365mm / 75mm drop M:365mm / 75mm drop L:410mm / 100mm drop
SADDLE	Liv Approach
PEDALS	N/A
DRIVETRAIN	
SHIFTERS	SRAM Apex 1, 1x12
FRONT DERAILLEUR	N/A
REAR DERAILLEUR	SRAM Apex XPLR
BRAKES	SRAM Apex hydraulic, Giant MPH rotors [F]160mm, [R]160mm
BRAKE LEVERS	SRAM Apex hydraulic, left lever dropper switch
CASSETTE	SRAM PG-1231 D1 XPLR, 12-speed, 11x44
CHAIN	SRAM Apex D1
CRANKSET	SRAM Apex 1 Wide DUB, 40t XS: 165mm, S: 170mm, M: 172.5mm, L: 172.5mm
BOTTOM BRACKET	SRAM DUB, press fit

WHEELS	
RIMS	Giant P-X2 Disc, alloy
HUBS	Giant alloy, 12mm thru-axle
SPOKES	Sapim
TYRES	Giant Crosscut Grip, 700x45c, tubeless
EXTRAS	Tubeless prepared, 53mm max tyre size in "long" flip chip position, 45mm max tyre size in "short" flip chip position

Price: \$4,199.00

GEOMETRY

FRAME	XS	S	M	L
	SHORT LONG	SHORT LONG	SHORT LONG	SHORT LONG
Seat Tube Length (mm)	390	420	465	500
Seat Tube Angle	74.5° 74.4°	74.5° 74.4°	74.5° 74.4°	74.5° 74.4°
Top Tube Length (mm)	525 525	535 535	545 545	555 555
Head Tube Length (mm)	90	110	140	160
Head Tube Angle	70.0° 69.9°	70.5° 70.4°	71.0° 70.9°	71.0° 70.9°
Fork Rake (mm)	50	50	50	50
Trail (mm)	78.4 82	75 78.5	71.6 75.1	71.6 75
Wheelbase (mm)	1012 1022	1019 1029	1026 1036	1043 1052
Chain Stay Length (mm)	425 435	425 435	425 435	430 440
Bottom Bracket Drop (mm)	80 81	80 81	80 81	80 81
Stack (mm)	523 524	544 545	574 575	593 594
Reach (mm)	380 379	384 383	386 385	391 389
Stand Over Height (mm)	681 688	708 715	748 755	779 786
Stem Length (mm)	50	60	70	80
Crank Length (mm)	165	170	172.5	172.5
Wheel Size	700	700	700	700

Please note that our specifications may be impacted by running substitution changes, we highly recommend confirming the specifications of our products with your local retailer at the time of sale if purchasing in-store. *Recommended Retail Prices are subject to change without notice and may vary from store to store depending on freight and assembly costs.