

DEVOTE ADVANCED 1



SPECS

| FRAME | |
|-------------------------|--|
| SIZES | XS, S, M, L |
| COLOURS | Ice Age |
| FRAME | Advanced-grade composite, 12x142mm thru-axle, flat mount disc, flip chip – dropout, integrated down tube storage, integrated cable routing |
| FORK | Advanced-grade composite, full-composite OverDrive steerer, stainless steel bearings, 12mm thru-axle, flat mount disc |
| SHOCK | N/A |
| COMPONENTS | |
| HANDLEBAR | Giant Contact XR D-Fuse, 31.8mm, 5-degree back sweep, flare drop, alloy XS: 400mm, S: 400mm, M: 420mm, L: 420mm |
| GRIPS | Liv All Condition |
| STEM | Giant Contact AeroLight, -10 degree, alloy XS: 50mm, S: 60mm, M: 70mm, L: 80mm |
| SEATPOST | Post Moderne, dropper, 30mm suspension XS: 75mm, S: 75mm, M: 75mm, L: 100mm |
| SADDLE | Liv Approach |
| PEDALS | PEDALS NOT SUPPLIED |
| DRIVETRAIN | |
| SHIFTERS | SRAM Apex, 1x12 |
| FRONT DERAILLEUR | N/A |
| REAR DERAILLEUR | SRAM Apex XPLR |
| BRAKES | SRAM Apex hydraulic, Giant MPH rotors [F]160mm, [R]160mm |
| BRAKE LEVERS | SRAM Apex hydraulic, left lever dropper switch |
| CASSETTE | SRAM PG-1231 D1 XPLR, 12-speed, 11x44 |
| CHAIN | SRAM Apex 12SCN-APX-D1 |
| CRANKSET | SRAM Apex 1 Wide, 40t XS: 165mm, S: 170mm, M: 172.5mm, L: 172.5mm |
| BOTTOM BRACKET | SRAM DUB, press fit |

| WHEELS | |
|---------------------------|---|
| RIMS | Giant P-X2 Disc wheelset, alloy |
| HUBS | Giant alloy, 12mm thru-axle |
| SPOKES | Sapim |
| TYRES | Maxxis Rambler, 700x45c, tubeless |
| EXTRAS | Giant 1x chain guide, factory tubeless set up, ISC clamp, integrated down tube storage bag |
| LIMITS | |
| COMPATIBILITY | Not compatible with RGX Fender |
| MAX TYRE CLEARANCE | 53mm max tyre size in long flip chip position, 45mm max tyre size in short flip chip position |
| MAX CHAINRING SIZE | SRAM Wide 2x 43-30, 1x 44T. Shimano GRX 2x 48-31, 1x 42T |

Price: £3,099.00

GEOMETRY

| FRAME | XS | | S | | M | | L | |
|--------------------------|---------------|---------------|---------------|---------------|-------|------|-------|------|
| | SHORT | LONG | SHORT | LONG | SHORT | LONG | SHORT | LONG |
| Seat Tube Length (mm) | 390 | 420 | 465 | 500 | | | | |
| Seat Tube Angle | 74.5° 74.4° | 74.5° 74.4° | 74.5° 74.4° | 74.5° 74.4° | | | | |
| Top Tube Length (mm) | 525 525 | 535 535 | 545 545 | 555 555 | | | | |
| Head Tube Length (mm) | 90 | 110 | 140 | 160 | | | | |
| Head Tube Angle | 70.0° 69.9° | 70.5° 70.4° | 71.0° 70.9° | 71.0° 70.9° | | | | |
| Fork Rake (mm) | 50 | 50 | 50 | 50 | | | | |
| Trail (mm) | 78.4 82 | 75 78.5 | 71.6 75.1 | 71.6 75 | | | | |
| Wheelbase (mm) | 1012 1022 | 1019 1029 | 1026 1036 | 1043 1052 | | | | |
| Chain Stay Length (mm) | 425 435 | 425 435 | 425 435 | 430 440 | | | | |
| Bottom Bracket Drop (mm) | 80 81 | 80 81 | 80 81 | 80 81 | | | | |
| Stack (mm) | 523 524 | 544 545 | 574 575 | 593 594 | | | | |
| Reach (mm) | 380 379 | 384 383 | 386 385 | 391 389 | | | | |
| Stand Over Height (mm) | 681 688 | 708 715 | 748 755 | 779 786 | | | | |
| Handlebar Width (mm) | 400 | 400 | 420 | 420 | | | | |
| Stem Length (mm) | 50 | 60 | 70 | 80 | | | | |
| Crank Length (mm) | 165 | 170 | 172.5 | 172.5 | | | | |
| Wheel Size | 700 | 700 | 700 | 700 | | | | |

Every effort has been made to ensure accuracy throughout this website. However, Giant reserves the right to change bike specifications, features, prices and colours without prior notice.