



DEVOTE ADVANCED 1



SPECS

FRAME	
SIZES	XS, S, M, L
COLOURS	Ice Age
FRAME	Advanced-grade composite, 12x142mm thru-axle, flat mount disc, flip chip – dropout, integrated down tube storage, integrated cable routing
FORK	Advanced-grade composite, full-composite OverDrive steerer, stainless steel bearings, 12mm thru-axle, flat mount disc
SHOCK	N/A
COMPONENTS	
HANDLEBAR	Giant Contact XR D-Fuse, 31.8mm, 5-degree back sweep, flare drop, alloy XS: 400mm, S: 400mm, M: 420mm, L: 420mm
GRIPS	Liv All Condition
STEM	Giant Contact AeroLight, -10 degree, alloy XS: 50mm, S: 60mm, M: 70mm, L: 80mm
SEATPOST	Post Moderne, dropper, 30mm suspension XS: 75mm, S: 75mm, M: 75mm, L: 100mm
SADDLE	Liv Approach
PEDALS	PEDALS NOT SUPPLIED
DRIVETRAIN	
SHIFTERS	SRAM Apex, 1x12
FRONT DERAILLEUR	N/A
REAR DERAILLEUR	SRAM Apex XPLR
BRAKES	SRAM Apex hydraulic, Giant MPH rotors [F]160mm, [R]160mm
BRAKE LEVERS	SRAM Apex hydraulic, left lever dropper switch
CASSETTE	SRAM PG-1231 D1 XPLR, 12-speed, 11x44
CHAIN	SRAM Apex 12SCN-APX-D1
CRANKSET	SRAM Apex 1 Wide, 40t XS: 165mm, S: 170mm, M: 172.5mm, L: 172.5mm
BOTTOM BRACKET	SRAM DUB, press fit

WHEELS	
RIMS	Giant P-X2 Disc wheelset, alloy
HUBS	Giant alloy, 12mm thru-axle
SPOKES	Sapim
TYRES	Maxxis Rambler, 700x45c, tubeless
EXTRAS	Giant 1x chain guide, factory tubeless set up, 53mm max tyre size in long flip chip position, 45mm max tyre size in short flip chip position, ISC clamp, integrated down tube storage bag
LIMITS	
MAX CHAINRING SIZE	SRAM Wide 2x 43-30, 1x 44T. Shimano GRX 2x 48-31, 1x 42T

Price: €3,549.00

GEOMETRY

FRAME	XS	S	M
	SHORT LONG	SHORT LONG	SHORT LONG
Seat Tube Length (mm)	390	420	465
Seat Tube Angle	74.5° 74.4°	74.5° 74.4°	74.5° 74.4°
Top Tube Length (mm)	525 525	535 535	545 545
Head Tube Length (mm)	90	110	140
Head Tube Angle	70.0° 69.9°	70.5° 70.4°	71.0° 70.9°
Fork Rake (mm)	50	50	50
Trail (mm)	78.4 82	75 78.5	71.6 75.1
Wheelbase (mm)	1012 1022	1019 1029	1026 1036
Chain Stay Length (mm)	425 435	425 435	425 435
Bottom Bracket Drop (mm)	80 81	80 81	80 81
Stack (mm)	523 524	544 545	574 575
Reach (mm)	380 379	384 383	386 385
Stand Over Height (mm)	681 688	708 715	748 755
Handlebar Width (mm)	400	400	420
Stem Length (mm)	50	60	70
Crank Length (mm)	165	170	172.5
Wheel Size	700	700	700

All specifications listed are subject to change without notice.