DEVOTE ADVANCED 1



ESPECIFICACIONES

CUADRO	
TALLAS	XS, S, M, L
COLORES	Lavender Blush
CUADRO	Advanced-grade composite, 12x142mm thru-axle, flat mount disc, flip chip – dropout, integrated down tube storage
HORQUILLA	Advanced-grade composite, full-composite OverDrive steerer, 12mm thru-axle, flat mount disc, FSA stainless upper/lower bearings
COMPONENTES	
MANILLAR	Giant Contact XR D-Fuse, 31.8mm, 5-degree back sweep, flare drop, XS: 400mm, S: 400mm, M: 420mm, L: 420mm
PUÑOS	Liv All Condition
POTENCIA	Giant Contact AeroLight, -10-degree, XS: 50mm, S: 60mm, M: 70mm, L: 80mm
TIJA DE SILLÍN	Post Moderne, dropper, 30mm suspension, XS: 75mm, S: 75mm, M: 75mm, L: 100mm
SILLÍN	Liv Grit
TRANSMISIÓN	
MANETAS DE CAMBIO	SRAM Apex 1, 1x12
DESVIADOR	N/A
CAMBIO TRASERO	SRAM Apex XPLR
FRENOS	SRAM Apex hydraulic, Giant MPH rotors, [F]160mm, [R]160mm
PALANCAS DE FRENOS	SRAM Apex hydraulic, left lever dropper switch
CASETTE	SRAM PG-1231 D1 XPLR, 12-speed, 11x44
CADENA	SRAM Apex 12SCN-APX-D1
JGO. PLATOS Y BIELAS	SRAM Apex 1 Wide DUB, 40t, XS: 165mm, S: 170mm, M: 172.5mm, L: 172.5mm
CAJA DE PEDALIER	SRAM DUB, press fit

RUEDAS	
LLANTAS	Giant P-X2 Disc, alloy
BUJES	Giant alloy, 12mm thru-axle
RADIOS	Sapim
CUBIERTAS	Giant Crosscut Grip, 700x45c, tubeless
EXTRAS	Giant 1x chain guide, tubeless prepared, 53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position, ISC clamp, in-frame storage bag
LÍMITES	
MÁXIMA ANCHURA DE NEUMÁTICO	53mm

Precio: 3.399,00 €

GEOMETRÍA

CUADRO	XS	S	M	L
	SHORT | LONG	SHORT | LONG	SHORT | LONG	SHORT | LONG
Longitud del tubo del sillín (mm)	390	420	465	500
Ángulo del tubo del sillín	74,5° | 74,4°	74,5° | 74,4°	74,5° | 74,4°	74,5° | 74,4°
Longitud del tubo superior (mm) (mm)	525 | 525	535 | 535	545 | 545	555 | 555
Longitud del tubo de dirección (mm) (mm)	90	110	140	160
Ángulo del tubo de dirección	70,0° | 69,9°	70,5° | 70,4°	71,0° | 70,9°	71,0° | 70,9°
Inclinación de la horquilla (mm)	50	50	50	50
Trail (mm) (mm)	78,4 | 82	75 | 78,5	71,6 | 75,1	71,6 | 75
Distancia entre ejes (mm) (mm)	1012 | 1022	1019 | 1029	1026 | 1036	1043 | 1052
Longitud de la vaina (mm) (mm)	425 | 435	425 | 435	425 | 435	430 | 440
Caída del eje de pedalier (mm) (mm)	80 | 81	80 | 81	80 | 81	80 | 81
Stack (mm) (mm)	523 | 524	544 | 545	574 | 575	593 | 594
Reach (mm) (mm)	380 | 379	384 | 383	386 | 385	391 | 389
Altura del suelo al tubo (mm) (mm)	681 | 688	708 | 715	748 | 755	779 | 786
Ancho del manillar (mm) (mm)	400	400	420	420
Longitud de la potencia (mm) (mm)	50	60	70	80
Longitud de las bielas (mm) (mm)	165	170	172,5	172,5

Giant se reserva el derecho a modificar especificaciones, precios o colores sin previo aviso.