



CARACTÉRISTIQUES TECHNIQUES

CADRE	
TAILLES	XS, S, M, L
COULEURS	Lavender Blush
CADRE	Advanced-grade composite, 12x142mm thru-axle, flat mount disc, flip chip – dropout, integrated down tube storage
FOURCHE	Advanced-grade composite, full-composite OverDrive steerer, 12mm thru-axle, flat mount disc, FSA stainless upper/lower bearings
COMPOSANTES	
GUIDON	Giant Contact XR D-Fuse, 31.8mm, 5-degree back sweep, flare drop, XS: 400mm, S: 400mm, M: 420mm, L: 420mm
POIGNÉES	Liv All Condition
POTENCE	Giant Contact AeroLight, -10-degree, XS: 50mm, S: 60mm, M: 70mm, L: 80mm
TIGE DE SELLE	Post Moderne, dropper, 30mm suspension, XS: 75mm, S: 75mm, M: 75mm, L: 100mm
SELLE	Liv Grit
TRANSMISSION (DRIVETRAIN)	
LEVIERS DE VITESSE	SRAM Apex 1, 1x12
DÉRAILLEUR AVANT	N/A
DÉRAILLEUR ARRIÈRE	SRAM Apex XPLR
FREINS	SRAM Apex hydraulic, Giant MPH rotors, [F]160mm, [R]160mm
LEVIERS DE FREIN	SRAM Apex hydraulic, left lever dropper switch
CASSETTE	SRAM PG-1231 D1 XPLR, 12-speed, 11x44
CHAÎNE	SRAM Apex 12SCN-APX-D1
PÉDALIER	SRAM Apex 1 Wide DUB, 40t, XS: 165mm, S: 170mm, M: 172.5mm, L: 172.5mm
BOÎTIER DE PÉDALIER	SRAM DUB, press fit

ROUES	
JANTES	Giant P-X2 Disc, alloy
MOYEUX	Giant alloy, 12mm thru-axle
RAYONS	Sapim
PNEUS	Giant Crosscut Grip, 700x45c, tubeless
EXTRAS	Giant 1x chain guide, tubeless prepared, 53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position, ISC clamp, in-frame storage bag
LIMITES	
MAX TIRE CLEARANCE	53mm

Prix de détail: 3 999,00 \$

GÉOMÉTRIE

CADRE	XS	S	M	L
	SHORT LONG	SHORT LONG	SHORT LONG	SHORT LONG
Longueur du tube de selle (mm)	390	420	465	500
Angle du tube de selle	74,5° 74,4°	74,5° 74,4°	74,5° 74,4°	74,5° 74,4°
Longueur du tube supérieur (top tube) (mm)	525 525	535 535	545 545	555 555
Longueur du tube de direction (head tube) (mm)	90	110	140	160
Angle du tube de direction	70,0° 69,9°	70,5° 70,4°	71,0° 70,9°	71,0° 70,9°
Déport (rake) de fourche (mm)	50	50	50	50
Trail (mm)	78,4 82	75 78,5	71,6 75,1	71,6 75
Empattement (mm)	1012 1022	1019 1029	1026 1036	1043 1052
Longueur des bases (mm)	425 435	425 435	425 435	430 440
Hauteur du boîtier de pédalier (mm)	80 81	80 81	80 81	80 81
Portée Verticale (Stack) (mm)	523 524	544 545	574 575	593 594
Portée Horizontale (Reach) (mm)	380 379	384 383	386 385	391 389
Hauteur du cadre (mm)	681 688	708 715	748 755	779 786
Largeur du Guidon (mm)	400	400	420	420
Longueur de la Potence (mm)	50	60	70	80
Longueur des manivelles (mm)	165	170	172,5	172,5

Giant Canada se réserve le droit de modifier les spécifications sans préavis. Photos non contractuelles.