

DEVOTE ADVANCED 1



TECHNIQUES

CADRE	
TAILLES	XS, S, M, L
COLORIS	Ice Age
CADRE	Advanced-grade composite, 12x142mm thru-axle, flat mount disc, flip chip - dropout, integrated down tube storage
FOURCHE	Advanced-grade composite, full-composite OverDrive steerer, 12mm thru-axle, flat mount disc, FSA stainless upper/lower bearings
AMORTISSEUR	N/A
COMPOSANTS	
CINTRE	Giant Contact XR D-Fuse, 31.8mm, 5-degree backsweep, flare drop XS: 400mm, S: 400mm, M: 420mm, L: 420mm
POIGNÉES	Liv All Condition
POTENCE	Giant Contact AeroLight, -10-degree XS: 50mm, S: 60mm, M: 70mm, L: 80mm
TIGE DE SELLE	Post Moderne, dropper, 30mm suspension XS: 75mm, S: 75mm, M: 75mm, L: 100mm
SELLE	Liv Approach
PÉDALES	N/A
DÉRAILLEUR	
MANETTES	SRAM Apex 1, 1x12
DÉRAILLEUR AVANT	N/A
DÉRAILLEUR ARRIÈRE	SRAM Apex XPLR
FREINS	SRAM Apex hydraulic, Giant MPH rotors [F]160mm, [R]160mm
LEVIER DE FREIN	SRAM Apex hydraulic, left lever dropper switch
CASSETTE	SRAM PG-1231 D1 XPLR, 12-speed, 11x44
CHAÎNE	SRAM Apex 12SCN-APX-D1
PÉDALIER	SRAM Apex 1 Wide DUB, 40t XS: 165mm, S: 170mm, M: 172.5mm, L: 172.5mm
BOITIER DE PÉDALIER	SRAM DUB, press fit

ROUES	
JANTES	Giant P-X2 Disc, alloy
MOYEUX	Giant alloy, 12mm thru-axle
RAYONS	Sapim
PNEUS	Giant Crosscut Grip, 700x45c, tubeless
EXTRAS	Giant 1x chain guide, tubeless prepared, 53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position, ISC clamp, in-frame storage bag
ACCESSOIRES	
ECLAIRAGE	Kit d'éclairage avant et arrière à piles

Prix Public Conseillé: 3 300,00 €

GÉOMÉTRIE

CADRE	XS		S		M		L	
	SHORT	LONG	SHORT	LONG	SHORT	LONG	SHORT	LONG
Longueur de tube de selle (mm)	390	420	465	500				
Angle de tube de selle	74,5° 74,4°	74,5° 74,4°	74,5° 74,4°	74,5° 74,4°				
Longueur du tube supérieur (mm)	525 525	535 535	545 545	555 555				
Longueur du tube de direction (mm)	90	110	140	160				
Angle du tube de direction	70,0° 69,9°	70,5° 70,4°	71,0° 70,9°	71,0° 70,9°				
Déport de fourche (mm)	50	50	50	50				
Trail (mm)	78,4 82	75 78,5	71,6 75,1	71,6 75				
Empattement (mm)	1012 1022	1019 1029	1026 1036	1043 1052				
Longueur des bases (mm)	425 435	425 435	425 435	430 440				
Drop du boîtier de pédalier (mm)	80 81	80 81	80 81	80 81				
Stack (mm)	523 524	544 545	574 575	593 594				
Reach (mm)	380 379	384 383	386 385	391 389				
Hauteur en statique (mm)	681 688	708 715	748 755	779 786				
Largeur de cintre (mm)	400	400	420	420				
Longueur de potence (mm)	50	60	70	80				
Longueur des manivelles (mm)	165	170	172,5	172,5				
Diamètre des roues	700	700	700	700				

Produits conformes aux exigences de sécurité (décret n° 2016-364 du 29 mars 2016). GIANT France se réserve le droit de modifier les spécifications sans préavis.