# DEVOTE ADVANCED 1



## SPECIFIKACIJE

| OKVIR | |
|---|---|
| **VELIČINE** | XS, S, M, L |
| **BOJE** | Ice Age |
| **OKVIR** | Advanced-grade composite, 12x142mm thru-axle, flat mount disc, flip chip – dropout, integrated down tube storage, integrated cable routing |
| **VILICA** | Advanced-grade composite, full-composite OverDrive steerer, stainless steel bearings, 12mm thru-axle, flat mount disc |
| **AMORTIZER** | N/A |
| **KOMPONENTE** | |
| **VOLAN** | Giant Contact XR D-Fuse, 31.8mm, 5-degree back sweep, flare drop, alloy XS: 400mm, S: 400mm, M: 420mm, L: 420mm |
| **GRIPS** | Liv All Condition |
| **LULA VOLANA** | Giant Contact AeroLight, -10 degree, alloy XS: 50mm, S: 60mm, M: 70mm, L: 80mm |
| **CIJEV SJEDALA** | Post Moderne, dropper, 30mm suspension XS: 75mm, S: 75mm, M: 75mm, L: 100mm |
| **SJEDALO** | Liv Approach |
| **PEDALE** | N/A |
| **POGON** | |
| **RUČICE MJENJAČA** | SRAM Apex, 1x12 |
| **PREDNJI MJENJAČ** | N/A |
| **STRAŽNJI MJENJAČ** | SRAM Apex XPLR |
| **KOČNICE** | SRAM Apex hydraulic, Giant MPH rotors [F]160mm, [R]160mm |
| **RUČICE KOČNICA** | SRAM Apex hydraulic, left lever dropper switch |
| **KAZETA** | SRAM PG-1231 D1 XPLR, 12-speed, 11x44 |
| **LANAC** | SRAM Apex 12SCN-APX-D1 |
| **POGON** | SRAM Apex 1 Wide, 40t XS: 165mm, S: 170mm, M: 172.5mm, L: 172.5mm |
| **OSOVINA POGONA (BB)** | SRAM DUB, press fit |

| KOTAČI | |
|---|---|
| **OBRUČI** | Giant P-X2 Disc wheelset, alloy |
| **NABE** | Giant alloy, 12mm thru-axle |
| **ŽBICE** | Sapim |
| **GUME** | Maxxis Rambler, 700x45c, tubeless |
| **DODACI** | Giant 1x chain guide, tubeless prepared, 53mm max tire size in long flip chip position, 45mm max tire size in short flip chip position, ISC clamp, integrated down tube storage bag |

## GEOMETRIJA

| OKVIR | XS | S | M |
|---|---|---|---|
| | SHORT \| LONG | SHORT \| LONG | SHORT \| L |
| Dužina cijevi sjedala (mm) | 390 | 420 | 465 |
| Kut cijevi sjedala | 74,5° \| 74,4° | 74,5° \| 74,4° | 74,5° \| 74 |
| Dužina gornje cijevi (mm) | 525 \| 525 | 535 \| 535 | 545 \| 545 |
| Dužina prednje cijevi (mm) | 90 | 110 | 140 |
| Kut vilice | 70,0° \| 69,9° | 70,5° \| 70,4° | 71,0° \| 70 |
| Zakrivljenost vilice (offset) (mm) | 50 | 50 | 50 |
| Staza (mm) | 78,4 \| 82 | 75 \| 78,5 | 71,6 \| 75, |
| Međuosovinski razmak kotača (mm) | 1012 \| 1022 | 1019 \| 1029 | 1026 \| 10 |
| Dužina od osovine pogona do osovine zadnjeg kotača (CS) (mm) | 425 \| 435 | 425 \| 435 | 425 \| 435 |
| Položaj osovine pogona (mm) | 80 \| 81 | 80 \| 81 | 80 \| 81 |
| Vertikalna dužina od osovine pogona do glave okvira (stack) (mm) | 523 \| 524 | 544 \| 545 | 574 \| 575 |
| Horizontalna dužina od osovine pogona do glave okvira (reach) (mm) | 380 \| 379 | 384 \| 383 | 386 \| 385 |
| Prekoračna visina (mm) | 681 \| 688 | 708 \| 715 | 748 \| 755 |
| Širina volana (mm) | 400 | 400 | 420 |
| Dužina lule volana (mm) | 50 | 60 | 70 |
| Dužina poluge pedale (mm) | 165 | 170 | 172,5 |
| Veličina kotača | 700 | 700 | 700 |

*Sve navedene specifikacije podložne su promjeni bez prethodne najave.*