

# DEVOTE ADVANCED 1



## SPECIFIKACIJE

OKVIR	
VELIČINE	XS, S, M, L
BOJE	Ice Age
OKVIR	Advanced-grade composite, 12x142mm thru-axle, flat mount disc, flip chip - dropout, integrated down tube storage
VILICA	Advanced-grade composite, full-composite OverDrive steerer, 12mm thru-axle, flat mount disc, FSA stainless upper/lower bearings
AMORTIZER	N/A
KOMPONENTE	
VOLAN	Giant Contact XR D-Fuse, 31.8mm, 5-degree backsweep, flare drop XS: 400mm, S: 400mm, M: 420mm, L: 420mm
GRIPS	Liv All Condition
LULA VOLANA	Giant Contact AeroLight, -10-degree XS: 50mm, S: 60mm, M: 70mm, L: 80mm
CIJEV SJEDALA	Post Moderne, dropper, 30mm suspension XS: 75mm, S: 75mm, M: 75mm, L: 100mm
SJEDALO	Liv Approach
POGON	
RUČICE MJENJAČA	SRAM Apex 1, 1x12
PREDNJI MJENJAČ	N/A
STRAŽNJI MJENJAČ	SRAM Apex XPLR
KOČNICE	SRAM Apex hydraulic, Giant MPH rotors [F]160mm, [R]160mm
RUČICE KOČNICA	SRAM Apex hydraulic, left lever dropper switch
KAZETA	SRAM PG-1231 D1 XPLR, 12-speed, 11x44
LANAC	SRAM Apex 12SCN-APX-D1
POGON	SRAM Apex 1 Wide DUB, 40t XS: 165mm, S: 170mm, M: 172.5mm, L: 172.5mm
OSOVINA POGONA (BB)	SRAM DUB, press fit

KOTAČI	
OBRUČI	Giant P-X2 Disc, alloy
NABE	Giant alloy, 12mm thru-axle
ŽBICE	Sapim
GUME	Giant Crosscut Grip, 700x45c, tubeless
DODACI	Giant 1x chain guide, tubeless prepared, 53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position, ISC clamp, in-frame storage bag

## GEOMETRIJA

OKVIR	XS	S	M
	SHORT   LONG	SHORT   LONG	SHORT   LONG
Dužina cijevi sjedala (mm)	390	420	465
Kut cijevi sjedala	74,5°   74,4°	74,5°   74,4°	74,5°   74,4°
Dužina gornje cijevi (mm)	525   525	535   535	545   545
Dužina prednje cijevi (mm)	90	110	140
Kut vilice	70,0°   69,9°	70,5°   70,4°	71,0°   70,9°
Zakrivljenost vilice (offset) (mm)	50	50	50
Staza (mm)	78,4   82	75   78,5	71,6   75,1
Međuosovinski razmak kotača (mm)	1012   1022	1019   1029	1026   1036
Dužina od osovine pogona do osovine zadnjeg kotača (CS) (mm)	425   435	425   435	425   435
Položaj osovine pogona (mm)	80   81	80   81	80   81
Vertikalna dužina od osovine pogona do glave okvira (stack) (mm)	523   524	544   545	574   575
Horizontalna dužina od osovine pogona do glave okvira (reach) (mm)	380   379	384   383	386   385
Prekoračna visina (mm)	681   688	708   715	748   755
Širina volana (mm)	400	400	420
Dužina lule volana (mm)	50	60	70
Dužina poluge pedale (mm)	165	170	172,5
Veličina kotača	700	700	700

Sve navedene specifikacije podložne su promjeni bez prethodne najave.