

DEVOTE ADVANCED 1



SPECIFIKACIJE

OKVIR	
VELIČINE	XS, S, M, L
BOJE	Lavender Blush
OKVIR	Advanced-grade composite, 12x142mm thru-axle, flat mount disc, flip chip - dropout, integrated down tube storage
VILICA	Advanced-grade composite, full-composite OverDrive steerer, 12mm thru-axle, flat mount disc, FSA stainless upper/lower bearings
KOMPONENTE	
VOLAN	Giant Contact XR D-Fuse, 31.8mm, 5-degree back sweep, flare drop, XS: 400mm, S: 400mm, M: 420mm, L: 420mm
GRIPS	Liv All Condition
LULA VOLANA	Giant Contact AeroLight, -10-degree, XS: 50mm, S: 60mm, M: 70mm, L: 80mm
CIJEV SJEDALA	Post Moderne, dropper, 30mm suspension, XS: 75mm, S: 75mm, M: 75mm, L: 100mm
SJEDALO	Liv Grit
POGON	
RUČICE MJENJAČA	SRAM Apex 1, 1x12
PREDNJI MJENJAČ	N/A
STRAŽNJI MJENJAČ	SRAM Apex XPLR
KOČNICE	SRAM Apex hydraulic, Giant MPH rotors, [F]160mm, [R]160mm
RUČICE KOČNICA	SRAM Apex hydraulic, left lever dropper switch
KAZETA	SRAM PG-1231 D1 XPLR, 12-speed, 11x44
LANAC	SRAM Apex 12SCN-APX-D1
POGON	SRAM Apex 1 Wide DUB, 40t, XS: 165mm, S: 170mm, M: 172.5mm, L: 172.5mm
OSOVINA POGONA (BB)	SRAM DUB, press fit

KOTAČI	
OBRUČI	Giant P-X2 Disc, alloy
NABE	Giant alloy, 12mm thru-axle
ŽBICE	Sapim
GUME	Giant Crosscut Grip, 700x45c, tubeless
DODACI	Giant 1x chain guide, tubeless prepared, 53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position, ISC clamp, in-frame storage bag
LIMITS	
MAX TIRE CLEARANCE	53mm

GEOMETRIJA

OKVIR	XS		S		M	
	SHORT	LONG	SHORT	LONG	SHORT	LONG
Dužina cijevi sjedala (mm)	390	420	420	465	465	510
Kut cijevi sjedala	74,5°	74,4°	74,5°	74,4°	74,5°	74,4°
Dužina gornje cijevi (mm)	525	525	535	535	545	545
Dužina prednje cijevi (mm)	90	110	110	140	140	170
Kut vilice	70,0°	69,9°	70,5°	70,4°	71,0°	70,9°
Zakrivljenost vilice (offset) (mm)	50	50	50	50	50	50
Staza (mm)	78,4	82	75	78,5	71,6	75,5
Međuosovinski razmak kotača (mm)	1012	1022	1019	1029	1026	1036
Dužina od osovine pogona do osovine zadnjeg kotača (CS) (mm)	425	435	425	435	425	435
Položaj osovine pogona (mm)	80	81	80	81	80	81
Vertikalna dužina od osovine pogona do glave okvira (stack) (mm)	523	524	544	545	574	575
Horizontalna dužina od osovine pogona do glave okvira (reach) (mm)	380	379	384	383	386	385
Prekoračna visina (mm)	681	688	708	715	748	755
Širina volana (mm)	400	400	400	420	420	420
Dužina lule volana (mm)	50	60	70	70	70	70
Dužina poluge pedale (mm)	165	170	170	172,5	172,5	172,5

Sve navedene specifikacije podložne su promjeni bez prethodne najave.