

DEVOTE ADVANCED 1



SPECS

FRAME	
SIZES	XS, S, M, L
COLORS	Lavender Blush
FRAME	Advanced-grade composite, 12x142mm thru-axle, flat mount disc, flip chip - dropout, integrated down tube storage
FORK	Advanced-grade composite, full-composite OverDrive steerer, 12mm thru-axle, flat mount disc, FSA stainless upper/lower bearings
COMPONENTS	
HANDLEBAR	Giant Contact XR D-Fuse, 31.8mm, 5-degree back sweep, flare drop, XS: 400mm, S: 400mm, M: 420mm, L: 420mm
GRIPS	Liv All Condition
STEM	Giant Contact AeroLight, -10-degree, XS: 50mm, S: 60mm, M: 70mm, L: 80mm
SEATPOST	Post Moderne, dropper, 30mm suspension, XS: 75mm, S: 75mm, M: 75mm, L: 100mm
SADDLE	Liv Grit
DRIVETRAIN	
SHIFTERS	SRAM Apex 1, 1x12
FRONT DERAILLEUR	N/A
REAR DERAILLEUR	SRAM Apex XPLR
BRAKES	SRAM Apex hydraulic, Giant MPH rotors, [F]160mm, [R]160mm
BRAKE LEVERS	SRAM Apex hydraulic, left lever dropper switch
CASSETTE	SRAM PG-1231 D1 XPLR, 12-speed, 11x44
CHAIN	SRAM Apex 12SCN-APX-D1
CRANKSET	SRAM Apex 1 Wide DUB, 40t, XS: 165mm, S: 170mm, M: 172.5mm, L: 172.5mm
BOTTOM BRACKET	SRAM DUB, press fit

WHEELS	
RIMS	Giant P-X2 Disc, alloy
HUBS	Giant alloy, 12mm thru-axle
SPOKES	Sapim
TIRES	Giant Crosscut Grip, 700x45c, tubeless
EXTRAS	Giant 1x chain guide, tubeless prepared, 53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position, ISC clamp, in-frame storage bag
LIMITS	
MAX TIRE CLEARANCE	53mm

GEOMETRY

FRAME	XS		S		M		L	
	SHORT	LONG	SHORT	LONG	SHORT	LONG	SHORT	LONG
Seat Tube Length (mm)	390	420	465	500				
Seat Tube Angle	74,5° 74,4°	74,5° 74,4°	74,5° 74,4°	74,5° 74,4°				
Top Tube Length (mm)	525 525	535 535	545 545	555 555				
Head Tube Length (mm)	90	110	140	160				
Head Tube Angle	70,0° 69,9°	70,5° 70,4°	71,0° 70,9°	71,0° 70,9°				
Fork Rake (mm)	50	50	50	50				
Trail (mm)	78,4 82	75 78,5	71,6 75,1	71,6 75				
Wheelbase (mm)	1012 1022	1019 1029	1026 1036	1043 1052				
Chain Stay Length (mm)	425 435	425 435	425 435	430 440				
Bottom Bracket Drop (mm)	80 81	80 81	80 81	80 81				
Stack (mm)	523 524	544 545	574 575	593 594				
Reach (mm)	380 379	384 383	386 385	391 389				
Stand Over Height (mm)	681 688	708 715	748 755	779 786				
Handlebar Width (mm)	400	400	420	420				
Stem Length (mm)	50	60	70	80				
Crank Length (mm)	165	170	172,5	172,5				

All specifications listed are subject to change without notice.