DEVOTE ADVANCED 1



SPECS

RAMME	
STØRRELSE	XS, S, M, L
FARGE	Ice Age
RAMME	Advanced-grade composite, 12x142mm thru-axle, flat mount disc, flip chip – dropout, integrated down tube storage, integrated cable routing
GAFFEL	Advanced-grade composite, full-composite OverDrive steerer, stainless steel bearings, 12mm thru-axle, flat mount disc
DEMPER	N/A
KOMPONENTER	
STYRE	Giant Contact XR D-Fuse, 31.8mm, 5-degree back sweep, flare drop, alloy XS: 400mm, S: 400mm, M: 420mm, L: 420mm
GRIPS	Liv All Condition
STYRSTEM	Giant Contact AeroLight, -10 degree, alloy XS: 50mm, S: 60mm, M: 70mm, L: 80mm
SETEPINNE	Post Moderne, dropper, 30mm suspension XS: 75mm, S: 75mm, M: 75mm, L: 100mm
SADEL	Liv Approach
PEDALER	N/A
DRIVVERK	
GIRHENDLER	SRAM Apex, 1x12
FRONTGIR	N/A
BAKGIR	SRAM Apex XPLR
BREMSER	SRAM Apex hydraulic, Giant MPH rotors [F]160mm, [R]160mm
BREMSEHENDLER	SRAM Apex hydraulic, left lever dropper switch
KASSETT	SRAM PG-1231 D1 XPLR, 12-speed, 11x44
KJEDE	SRAM Apex 12SCN-APX-D1
KRANK	SRAM Apex 1 Wide, 40t XS: 165mm, S: 170mm, M: 172.5mm, L: 172.5mm
BOTTOM BRACKET	SRAM DUB, press fit

HJUL	
FELG	Giant P-X2 Disc wheelset, alloy
NAV	Giant alloy, 12mm thru-axle
EIKE	Sapim
DEKK	Maxxis Rambler, 700x45c, tubeless
EXTRAS	Giant 1x chain guide, tubeless prepared, 53mm max tire size in long flip chip position, 45mm max tire size in short flip chip position, ISC clamp, integrated down tube storage bag

GEOMETRI

RAMME	XS	S	M	L
	SHORT | LONG	SHORT | LONG	SHORT | LONG	SHORT | LONG
Seat Tube Length (mm)	390	420	465	500
Seat Tube Angle	74,5° | 74,4°	74,5° | 74,4°	74,5° | 74,4°	74,5° | 74,4°
Top Tube Length (mm)	525 | 525	535 | 535	545 | 545	555 | 555
Head Tube Length (mm)	90	110	140	160
Head Tube Angle	70,0° | 69,9°	70,5° | 70,4°	71,0° | 70,9°	71,0° | 70,9°
Fork Rake (mm)	50	50	50	50
Trail (mm)	78,4 | 82	75 | 78,5	71,6 | 75,1	71,6 | 75
Wheelbase (mm)	1012 | 1022	1019 | 1029	1026 | 1036	1043 | 1052
Chain Stay Length (mm)	425 | 435	425 | 435	425 | 435	430 | 440
Bottom Bracket Drop (mm)	80 | 81	80 | 81	80 | 81	80 | 81
Stack (mm)	523 | 524	544 | 545	574 | 575	593 | 594
Reach (mm)	380 | 379	384 | 383	386 | 385	391 | 389
Stand Over Height (mm)	681 | 688	708 | 715	748 | 755	779 | 786
Handlebar Width (mm)	400	400	420	420
Stem Length (mm)	50	60	70	80
Crank Length (mm)	165	170	172,5	172,5
Wheel Size	700	700	700	700

Alle spesifikasjonene kan endres uten varsel.