DEVOTE ADVANCED 1



SPECS

QUADRO	
TAMANHOS	XS, S, M, L
CORES	Lavender Blush
QUADRO	Advanced-grade composite, 12x142mm thru-axle, flat mount disc, flip chip – dropout, integrated down tube storage
FORQUILHA	Advanced-grade composite, full-composite OverDrive steerer, 12mm thru-axle, flat mount disc, FSA stainless upper/lower bearings
COMPONENTES	
GUIADOR	Giant Contact XR D-Fuse, 31.8mm, 5-degree back sweep, flare drop, XS: 400mm, S: 400mm, M: 420mm, L: 420mm
PUNHOS	Liv All Condition
AVANÇO	Giant Contact AeroLight, -10-degree, XS: 50mm, S: 60mm, M: 70mm, L: 80mm
ESPIGÃO DE SELIM	Post Moderne, dropper, 30mm suspension, XS: 75mm, S: 75mm, M: 75mm, L: 100mm
SELIM	Liv Grit
TRANSMISSÃO	
MANETES	SRAM Apex 1, 1x12
DESVIADOR DIANTEIRO	N/A
DESVIADOR TRASEIRO	SRAM Apex XPLR
TRAVÕES	SRAM Apex hydraulic, Giant MPH rotors, [F]160mm, [R]160mm
MANÍPULOS DOS TRAVÕES	SRAM Apex hydraulic, left lever dropper switch
CASSETE	SRAM PG-1231 D1 XPLR, 12-speed, 11x44
CORRENTE	SRAM Apex 12SCN-APX-D1
CONJUNTO PEDALEIRO	SRAM Apex 1 Wide DUB, 40t, XS: 165mm, S: 170mm, M: 172.5mm, L: 172.5mm
MOVIMENTO CENTRAL	SRAM DUB, press fit

RODAS	
AROS	Giant P-X2 Disc, alloy
CUBOS	Giant alloy, 12mm thru-axle
RAIOS	Sapim
PNEUS	Giant Crosscut Grip, 700x45c, tubeless
EXTRAS	Giant 1x chain guide, tubeless prepared, 53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position, ISC clamp, in-frame storage bag
LIMITES	
FOLGA MÁXIMA DO PNEU	53mm

Preço: 2 999,00 €

GEOMETRIA

QUADRO	XS	S	M	L
	SHORT | LONG	SHORT | LONG	SHORT | LONG	SHORT | LONG
Comprimento do tubo do assento (mm)	390	420	465	500
Ângulo do tubo do assento	74,5° | 74,4°	74,5° | 74,4°	74,5° | 74,4°	74,5° | 74,4°
Comprimento do tubo superior (mm)	525 | 525	535 | 535	545 | 545	555 | 555
Comprimento do tubo principal (mm)	90	110	140	160
Ângulo do tubo principal	70,0° | 69,9°	70,5° | 70,4°	71,0° | 70,9°	71,0° | 70,9°
Garfo ancinho (mm)	50	50	50	50
Trilha (mm)	78,4 | 82	75 | 78,5	71,6 | 75,1	71,6 | 75
distância entre eixos (mm)	1012 | 1022	1019 | 1029	1026 | 1036	1043 | 1052
Comprimento Chain Stay (mm)	425 | 435	425 | 435	425 | 435	430 | 440
Suporte inferior (mm)	80 | 81	80 | 81	80 | 81	80 | 81
Pilha (mm)	523 | 524	544 | 545	574 | 575	593 | 594
Alcançar (mm)	380 | 379	384 | 383	386 | 385	391 | 389
Altura do standover (mm)	681 | 688	708 | 715	748 | 755	779 | 786
Largura do guidão (mm)	400	400	420	420
Comprimento da haste (mm)	50	60	70	80
Comprimento da Manivela (mm)	165	170	172,5	172,5

Todas as especificações apresentadas estão sujeitas a alterações sem aviso prévio.