

DEVOTE ADVANCED 1



ŠPECIFIKÁCIE

RÁM	
VELKOSTI	XS, S, M, L
FARBY	Lavender Blush
RÁM	Advanced-grade composite, 12x142mm thru-axle, flat mount disc, flip chip - dropout, integrated down tube storage
VIDLICA	Advanced-grade composite, full-composite OverDrive steerer, 12mm thru-axle, flat mount disc, FSA stainless upper/lower bearings
KOMPONENTY	
RIADIDLÁ	Giant Contact XR D-Fuse, 31.8mm, 5-degree back sweep, flare drop, XS: 400mm, S: 400mm, M: 420mm, L: 420mm
GRIPY	Liv All Condition
PREDSTAVEC	Giant Contact AeroLight, -10-degree, XS: 50mm, S: 60mm, M: 70mm, L: 80mm
SEDLOVKA	Post Moderne, dropper, 30mm suspension, XS: 75mm, S: 75mm, M: 75mm, L: 100mm
SEDADLO	Liv Grit
POHON	
RADENIE	SRAM Apex 1, 1x12
PREŠMYKAČ	N/A
PREHADZOVAČKA	SRAM Apex XPLR
BRZDY	SRAM Apex hydraulic, Giant MPH rotors, [F]160mm, [R]160mm
BRZDOVÉ PÁKY	SRAM Apex hydraulic, left lever dropper switch
KAZETA	SRAM PG-1231 D1 XPLR, 12-speed, 11x44
REŤAZ	SRAM Apex 12SCN-APX-D1
KLUKY	SRAM Apex 1 Wide DUB, 40t, XS: 165mm, S: 170mm, M: 172.5mm, L: 172.5mm
STREDOVÉ ZLOŽENIE	SRAM DUB, press fit

KOLESÁ	
RÁFIKY	Giant P-X2 Disc, alloy
NÁBOJE	Giant alloy, 12mm thru-axle
ŠPICE	Sapim
PNEUMATIKY	Giant Crosscut Grip, 700x45c, tubeless
DOPLNKY	Giant 1x chain guide, tubeless prepared, 53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position, ISC clamp, in-frame storage bag
LIMITY	
MAXIMÁLNA ŠÍRKA PNEUMATÍK	53mm

Cena: 3 499 €

GEOMETRIA

RÁM	XS	S	M	L
	SHORT LONG	SHORT LONG	SHORT LONG	SHORT LONG
Dĺžka sedlovej trubky (mm)	390	420	465	500
Uhol sedlovej trubky	74,5° 74,4°	74,5° 74,4°	74,5° 74,4°	74,5° 74,4°
Dĺžka hornej rámovej trubky (mm)	525 525	535 535	545 545	555 555
Dĺžka hlavovej trubky (mm)	90	110	140	160
Uhol hlavovej trubky	70,0° 69,9°	70,5° 70,4°	71,0° 70,9°	71,0° 70,9°
Offset vidlice (mm)	50	50	50	50
Trail (mm)	78,4 82	75 78,5	71,6 75,1	71,6 75
Rázvor (mm)	1012 1022	1019 1029	1026 1036	1043 1052
Dĺžka zadnej stavby (mm)	425 435	425 435	425 435	430 440
Rozdiel zadnej voči stredovej osi - BB DROP (mm)	80 81	80 81	80 81	80 81
Stack - výška riadenia (mm)	523 524	544 545	574 575	593 594
Reach (mm)	380 379	384 383	386 385	391 389
Výška rámu od zeme (mm)	681 688	708 715	748 755	779 786
Šírka riaditok (mm)	400	400	420	420
Dĺžka predstavca (mm)	50	60	70	80
Dĺžka klúku (mm)	165	170	172,5	172,5

Všetky ceny a špecifikácie sa môžu zmeniť bez predchádzajúceho upozornenia.