

DEVOTE ADVANCED 1



SPECIFIKACIJE

OKVIR	
VELIKOSTI	XS, S, M, L
BARVE	Lavender Blush
OKVIR	Advanced-grade composite, 12x142mm thru-axle, flat mount disc, flip chip – dropout, integrated down tube storage
VILICE	Advanced-grade composite, full-composite OverDrive steerer, 12mm thru-axle, flat mount disc, FSA stainless upper/lower bearings
KOMPONENTE	
KRMILO	Giant Contact XR D-Fuse, 31.8mm, 5-degree back sweep, flare drop, XS: 400mm, S: 400mm, M: 420mm, L: 420mm
GRIPS	Liv All Condition
OPORA KRMILA	Giant Contact AeroLight, -10-degree, XS: 50mm, S: 60mm, M: 70mm, L: 80mm
OPORA SEDEŽA	Post Moderne, dropper, 30mm suspension, XS: 75mm, S: 75mm, M: 75mm, L: 100mm
SEDEŽ	Liv Grit
POGON	
PRESTAVNE ROČICE	SRAM Apex 1, 1x12
PREDNJI MENJALNIK	N/A
ZADNJI MENJALNIK	SRAM Apex XPLR
ZAVORE	SRAM Apex hydraulic, Giant MPH rotors, [F]160mm, [R]160mm
ZAVORNE ROČICE	SRAM Apex hydraulic, left lever dropper switch
VERIŽNIK	SRAM PG-1231 D1 XPLR, 12-speed, 11x44
VERIGA	SRAM Apex 12SCN-APX-D1
GONILKE Z VERIŽNIKI	SRAM Apex 1 Wide DUB, 40t, XS: 165mm, S: 170mm, M: 172.5mm, L: 172.5mm
BOTTOM BRACKET	SRAM DUB, press fit

OBROČNIKI	
OBROČI	Giant P-X2 Disc, alloy
PESTA	Giant alloy, 12mm thru-axle
NAPERE	Sapim
PLAŠČI	Giant Crosscut Grip, 700x45c, tubeless
DODATKI	Giant 1x chain guide, tubeless prepared, 53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position, ISC clamp, in-frame storage bag
LIMITS	
MAX TIRE CLEARANCE	53mm

GEOMETRIJA

OKVIR	XS	S	M	L
	SHORT LONG	SHORT LONG	SHORT LONG	SHORT LONG
Dolžina sedežne cevi (mm)	390	420	465	500
Kot sedežne cevi	74,5° 74,4°	74,5° 74,4°	74,5° 74,4°	74,5° 74,4°
Top Tube Length (mm)	525 525	535 535	545 545	555 555
Višina glave okvirja (mm)	90	110	140	160
Krmlilni kot	70,0° 69,9°	70,5° 70,4°	71,0° 70,9°	71,0° 70,9°
Zamik vpetja osi (mm)	50	50	50	50
Trail (mm)	78,4 82	75 78,5	71,6 75,1	71,6 75
Medosna razdalja (mm)	1012 1022	1019 1029	1026 1036	1043 1052
Dolžina cevi ob verigi (mm)	425 435	425 435	425 435	430 440
Bottom Bracket Drop (mm)	80 81	80 81	80 81	80 81
Oddaljenost zgornje cevi od gonilne osi (mm)	523 524	544 545	574 575	593 594
Doseg (mm)	380 379	384 383	386 385	391 389
Višina zgornje cevi (mm)	681 688	708 715	748 755	779 786
Širina krmila (mm)	400	400	420	420
Dolžina opore krmila (mm)	50	60	70	80
Dolžina gonilke (mm)	165	170	172,5	172,5

Vse navedene specifikacije se lahko spremenijo brez obvestila.