

# DEVOTE ADVANCED 2



## СПЕЦИФИКАЦИИ

РАМКА	
РАЗМЕР	XS, S, M, L
ЦВЯТ	Lunar Eclipse
РАМКА	Advanced-grade composite, 12x142mm thru-axle, flat mount disc, flip chip - dropout, integrated down tube storage
ВИЛКА	Advanced-grade composite, full-composite OverDrive steerer, 12mm thru-axle, flat mount disc, FSA stainless upper/lower bearings
ЗАДЕН АМОРТИСЬОР	N/A
КОМПОНЕНТИ	
КОРМИЛО	Giant Contact XR D-Fuse, 31.8mm, 5-degree back sweep, flare drop, XS: 400mm, S: 400mm, M: 420mm, L: 420mm
ГРИПОВЕ	Liv All Condition
ЛАПА	Giant Contact AeroLight, -10-degree, XS: 50mm, S: 60mm, M: 70mm, L: 80mm
КОЛЧЕ ЗА СЕДАЛКА	Giant D-Fuse, composite, 14mm offset
СЕДАЛКА	Liv Grit
DRIVETRAIN	
КОМАНДИ	Shimano GRX RX-610, 2x12
ПРЕДЕН ДЕРАЙЛЪОР	Shimano GRX RX-820
ЗАДЕН ДЕРАЙЛЪОР	Shimano GRX RX-820
СПИРАЧКИ	Shimano GRX BR-RX410 hydraulic, Giant MPH rotors, [F]160mm, [R]160mm
РЪКОХВАТКИ ЗА СПИРАЧКИ	Shimano GRX RX-610 hydraulic
КАСЕТА	Shimano CS-HG710, 12-speed, 11x36
ВЕРИГА	KMC X12L-1
КУРБЕЛ	Shimano FC-RX610, 30/46, XS: 165mm, S: 170mm, M: 172.5mm, L: 172.5mm
СРЕДНА КАСЕТА	Shimano, press fit

КАПЛИ	
ШИНИ	Giant P-X2 Disc, alloy
ГЛАВИНИ	Giant alloy, 12mm thru-axle
СПИЦИ	Sapim
ГУМИ	Giant Crosscut Grip, 700x45c, tubeless
ЕКСТРИ	53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position, tubeless prepared, ISC clamp, in-frame storage bag
ЛИМИТИ	
MAX TIRE CLEARANCE	53mm

## ГЕОМЕТРИЯ

РАМКА	XS	S	M	L
	SHORT   LONG	SHORT   LONG	SHORT   LONG	SHORT   LONG
Seat Tube Length (mm)	390	420	465	500
Seat Tube Angle	74,5°   74,4°	74,5°   74,4°	74,5°   74,4°	74,5°   74,4°
Top Tube Length (mm)	525   525	535   535	545   545	555   555
Head Tube Length (mm)	90	110	140	160
Head Tube Angle	70,0°   69,9°	70,5°   70,4°	71,0°   70,9°	71,0°   70,9°
Fork Rake (mm)	50	50	50	50
Trail (mm)	78,4   82	75   78,5	71,6   75,1	71,6   75
Wheelbase (mm)	1012   1022	1019   1029	1026   1036	1043   1052
Chain Stay Length (mm)	425   435	425   435	425   435	430   440
Bottom Bracket Drop (mm)	80   81	80   81	80   81	80   81
Stack (mm)	523   524	544   545	574   575	593   594
Обсер (mm)	380   379	384   383	386   385	391   389
Stand Over Height (mm)	681   688	708   715	748   755	779   786
Ширина на Кормило (mm)	400	400	420	420
Дължина на Лапа (mm)	50	60	70	80
Дължина на Курбел (mm)	165	170	172,5	172,5

All specifications listed are subject to change without notice.