

DEVOTE ADVANCED 2



SPECS

FRAME	
SIZES	XS, S, M, L
COLORS	Kelp Forest
FRAME	Advanced-grade composite, 12x142mm thru-axle, flat mount disc, flip chip – dropout, integrated down tube storage, integrated cable routing
FORK	Advanced-grade composite, full-composite OverDrive steerer, stainless steel bearings, 12mm thru-axle, flat mount disc
SHOCK	N/A
COMPONENTS	
HANDLEBAR	Giant Contact XR D-Fuse, 31.8mm, 5-degree back sweep, flare drop, alloy XS: 400mm, S: 400mm, M: 420mm, L: 420mm
GRIPS	Liv All Condition
STEM	Giant Contact AeroLight, -10 degree, alloy XS: 50mm, S: 60mm, M: 70mm, L: 80mm
SEATPOST	Giant Contact D-Fuse, composite, 14mm offset
SADDLE	Liv Approach
PEDALS	N/A
DRIVETRAIN	
SHIFTERS	Shimano GRX RX-610, 2x12
FRONT DERAILLEUR	Shimano GRX RX-820
REAR DERAILLEUR	Shimano GRX RX-820
BRAKES	Shimano GRX BR-RX410 hydraulic, Giant MPH rotors [F]160mm, [R]160mm
BRAKE LEVERS	Shimano GRX RX-610 hydraulic
CASSETTE	Shimano 105, 12-speed, 11x36
CHAIN	KMC X12L-1
CRANKSET	FSA Omega Modular AGX+, 32/48 XS: 165mm, S: 170mm, M: 172.5mm, L: 172.5mm
BOTTOM BRACKET	FSA, press fit

WHEELS	
RIMS	Giant P-X2 Disc wheelset, alloy
HUBS	Giant alloy, 12mm thru-axle
SPOKES	Sapim
TIRES	Maxxis Rambler, 700x40c, tubeless
EXTRAS	53mm max tire size in long flip chip position, 45mm max tire size in short flip chip position, tubeless prepared, ISC clamp, integrated down tube storage bag

GEOMETRY

FRAME	XS	S	M	L
	SHORT LONG	SHORT LONG	SHORT LONG	SHORT LONG
Seat Tube Length (mm)	390	420	465	500
Seat Tube Angle	74,5° 74,4°	74,5° 74,4°	74,5° 74,4°	74,5° 74,4°
Top Tube Length (mm)	525 525	535 535	545 545	555 555
Head Tube Length (mm)	90	110	140	160
Head Tube Angle	70,0° 69,9°	70,5° 70,4°	71,0° 70,9°	71,0° 70,9°
Fork Rake (mm)	50	50	50	50
Trail (mm)	78,4 82	75 78,5	71,6 75,1	71,6 75
Wheelbase (mm)	1012 1022	1019 1029	1026 1036	1043 1052
Chain Stay Length (mm)	425 435	425 435	425 435	430 440
Bottom Bracket Drop (mm)	80 81	80 81	80 81	80 81
Stack (mm)	523 524	544 545	574 575	593 594
Reach (mm)	380 379	384 383	386 385	391 389
Stand Over Height (mm)	681 688	708 715	748 755	779 786
Handlebar Width (mm)	400	400	420	420
Stem Length (mm)	50	60	70	80
Crank Length (mm)	165	170	172,5	172,5
Wheel Size	700	700	700	700

All specifications listed are subject to change without notice.